



Product Data

Syntilo CR 4

Synthetic coolant

Description

Castrol Syntilo™ CR 4 is a synthetic coolant which has been developed for tungsten carbide grinding. Further it can be used for general grinding of ferrous metals. It forms a clear, stable solution in both hard and soft waters. Syntilo CR 4 exhibits good anti-corrosion properties coupled with long system life.

Application

Syntilo CR 4 is developed for surface, cylindrical, double disk and centreless grinding especially of tungsten carbide.

Advantages

- Minimizes cobalt build-up which can lead to health hazards and tool/part failures
- Improves surface finish of components through reduced cobalt dissolution from the tungsten carbide binder matrix
- Low foaming in all water conditions to ensure continuous grinding performance
- Inhibits microbial growth to extend fluid life in central systems and individual sumps
- Rejects tramp oil to the surface of the fluid for easy removal
- Chlorine, phenol and nitrite free for environmental compliance
- Excellent corrosion protection even in hard water
- Settles chips quickly to prevent grinding wheel build-up and maintain a clean working environment
- Low residue tendency even at long sump life
- Boron, chlorine, phenol and nitrite free for environmental compliance

Typical Characteristics

Name	Test Method	Unit	Syntilo CR 4
<u>CONCENTRATE</u>			
Appearance	Visual		Transparent, yellow
Density @ 20°C / 68°F	DIN 51575	kg/m³	1.13
Mineral Oil content	calculated	Vol. %	0
<u>SOLUTION</u>			
Appearance	Visual		Transparent
pH (5%)	DIN 51361		9,2
Factor Refractometer			1,4

Recommended Concentrations

Grinding: 5-6%

Water range: 50–400 ppm CaCO₃

Storage

To avoid product deterioration always keep the container/drum tightly sealed. Store the product in a cool, dry place away from direct sunlight. Prevent exposure to frost and avoid water ingress. For optimum product stability, it is preferable to store the product indoors between 5°C and 45 °C / 41°F and 113°F.

For more details, please refer the product safety data sheet.

Syntilo CR 4

18 Dec 2014

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial, Technology Centre , Whitchurch Hill , Pangbourne , Reading , RG8 7QR , United Kingdom

<http://msdspds.castrol.com>