

Techniclean MTC 43

Machine tool and system cleaner

Description

Castrol Techniclean™ MTC 43 is a liquid, mildly alkaline, medium to heavy duty machine tool and system cleaner, based upon powerful low foaming surfactants, emulsifiers and anti-microbiological agents.

Application

Techniclean MTC 43 has been specifically formulated to deal with a wide variety of machine tool and system contaminants including fatty build-up in pipelines and floor ducts. Techniclean MTC 43 is easy to use with minimum disruption to production, being added directly to the coolant system whilst still in operation. Floating tramp oil is emulsified.

Conditions of Use

- An addition of 1 - 3% of Techniclean MTC 43 is recommended. The amount added depends on the general condition of the coolant system (1% is usually adequate)
- Introduce Techniclean MTC 43 where there is a good coolant movement, e.g. immediately beyond the pump outflow back to the main settling tank, or direct into a velocity trench or floor return channel. This ensures complete mixing with the coolant.
- Add Techniclean MTC 43 8 - 24 hours before the coolant is scheduled to be discarded. The machine tools should then be operated normally for a minimum of eight hours.
- Machine tools, which are not wetted by the emulsion, could be cleaned manually by using a 2 - 3% dilution of Techniclean MTC 43.
- Following this period of circulation (max 24 hours), empty the entire coolant system and machines and dispose of the coolant in accordance with normal work procedures.
- Rinsing with a fresh coolant (about 1%) is recommended.

Advantages

- Low foam and compatible with common soluble coolants and metal substrates – can be used whilst machines are operating normally which reduces maintenance and disposal costs
- Keeps machine tool systems in a clean and efficient condition – minimises downtime and so improves productivity
- Highly effective against bacteria and fungi contaminations – improves environment for workforce

Typical Characteristics

Name	Method	Units	Value
Appearance	Visual	-	clear, slight yellow to amber liquid
Density @ 20 °C	DIN 51 757	kg/m ³	1060
pH (5% dilution)	-	-	8.8

Subject to usual manufacturing tolerances.

User Advice

Care should be taken with handling the Techniclean MTC 43 concentrate to avoid eye and skin contact. Although it is not

expected that the risks of exposure to metalworking fluid will change as a result of the addition of Techniclean MTC 43, it is recommended that the normal appropriate handling precautions are used to avoid skin and eye contact with the fluid during this period.

Storage

To avoid product deterioration always keep the container/drum tightly sealed. Store the product in a cool, dry place away from direct sunlight. Prevent exposure to frost and avoid water ingress. For optimum product stability, it is preferable to store the product indoors between 5°C and 45 °C.

For more details, please refer the product safety data sheet.

Techniclean MTC 43

29 Jul 2015

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol Australia, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Australia Pty Limited - ABN 87 008 459 407 – 717 Bourke Street, Docklands Vic 3008

Technical Advice Line: 1300 557 998 Customer Service: 1300 722 088

<http://msdspdscastrol.com>

Page: 2/2