



## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.01.2020

Version number 7

Revision: 26.09.2019

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: Petromark® Instant Gasket Black 200ml - 10421**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**
  - SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
  - SU21 Consumer uses: Private households / general public / consumers
- **Application of the substance / the mixture**
  - One component temperature resistant silicone sealing for high temperature application
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
  - Petromark Automotive Chemicals
  - Rooswijkweg 316
  - 1951 ME Velsen-Noord, The Netherlands
  - www.petromark.eu
  - info@petromark.eu
  - Tel. +31 (0)251 211397
- **Further information obtainable from:**
  - Product safety department.
  - info@petromark.eu
- **1.4 Emergency telephone number:** During normal business hours: Tel. +31 (0)251 211397

### SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
  - The product is tested according 92/69/EC and is not classified as irritating to skin and eyes.
  - Aerosol 3 H229 Pressurised container: May burst if heated.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
  - The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms** Void
- **Signal word** Warning
- **Hazard statements**
  - H229 Pressurised container: May burst if heated.
- **Precautionary statements**
  - P101 If medical advice is needed, have product container or label at hand.
  - P102 Keep out of reach of children.
  - P103 Read label before use.
  - P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
  - P251 Do not pierce or burn, even after use.
  - P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
  - P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **2.3 Other hazards** not applicable
- **Results of PBT and vPvB assessment**

**• PBT:**

540-97-6 dodecamethylcyclhexasiloxane (D6)

**• vPvB:**

540-97-6 dodecamethylcyclhexasiloxane (D6)

### SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 2)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.01.2020

Version number 7

Revision: 26.09.2019

**Trade name: Petromark® Instant Gasket Black 200ml - 10421**

(Contd. of page 1)

## Dangerous components:

CAS: 29118-24-9 ELINCS: 471-480-0 Reg.nr.: 01-0000019758-54-xxxx	trans-1,3,3,3-Tetrafluoroprop-1-ene ⚠ Press. Gas C, H280	1-2.5%
CAS: 4253-34-3 EINECS: 224-221-9 Reg.nr.: 01-2119962266-32-xxxx	methylsilanetriyl triacetate ⚠ Skin Corr. 1B, H314; ⚠ Acute Tox. 4, H302	1-2.5%
CAS: 17865-07-5 EINECS: 241-816-9 Reg.nr.: 01-2119966899-07-xxxx	Propyltriacetoxysilan ⚠ Skin Corr. 1B, H314	1-2.5%
CAS: 540-97-6 EINECS: 208-762-8 Reg.nr.: 01-2119517435-42-xxx	dodecamethylcyclhexasiloxane (D6) Non-classified vPvB substance. Non-classified PBT substance.	<1%

## SVHC

540-97-6 dodecamethylcyclhexasiloxane (D6)

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information:

In case of accident or if you feel unwell, seek medical advice (show label or MSDS if possible).

**After inhalation:** No treatment necessary if the product is used normally.

#### After skin contact:

Treat affected skin with cotton wool or cellulose. Then wash and rinse thoroughly with water and a mild cleaning agent.

#### After eye contact:

Rinse opened eye for several minutes under running water. Remove contact lenses, if present and easy to do. Continue rinsing. Then consult a doctor.

**After swallowing:** If symptoms persist consult doctor.

### 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

### 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray.

Foam

**For safety reasons unsuitable extinguishing agents:** Water with full jet

### 5.2 Special hazards arising from the substance or mixture

Danger of bursting by heating.

In case of fire, the following can be released:

Carbon monoxide (CO)

### 5.3 Advice for firefighters

**Protective equipment:** Wear self-contained respiratory protective device.

#### Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Cool endangered receptacles with water spray and remove it out of emergency area if possible.

GB

(Contd. on page 3)



## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.01.2020

Version number 7

Revision: 26.09.2019

**Trade name: Petromark® Instant Gasket Black 200ml - 10421**

(Contd. of page 2)

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective clothing.  
Particular danger of slipping on leaked/spilled product.
- **6.2 Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.
- **6.3 Methods and material for containment and cleaning up:**  
Pick up mechanically.  
Dispose of the material collected according to regulations.  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
No dangerous substances are released.  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care.
- **Information about fire - and explosion protection:**  
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store only in the original receptacle.  
Do not store in gangways or stairways.  
Store in a cool location under dry conditions in well sealed receptacles  
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:**  
Do not store together with oxidizing and selfigniting materials.
- **Further information about storage conditions:**  
Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.  
Do not store together with oxidizing and self-igniting material.

### SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**  
During the curing small amount of acetic acid will be released.

**• DNELs****29118-24-9 trans-1,3,3,3-Tetrafluoroprop-1-ene**

Inhalative	wrks, long, system	3,902 mg/m <sup>3</sup> (mouse)
	cstm, long, system	830 mg/m <sup>3</sup> (mouse)

**4253-34-3 methylsilanetriyl triacetate**

Oral	cstm, long, system, oral	1 mg/kg/d (mouse)
	cstm, short, system	1 mg/kg bw/d (rabbit)
Dermal	wrks, long, system	14.5 mg/kg/d (mouse)

(Contd. on page 4)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 14.01.2020

Version number 7

Revision: 26.09.2019

**Trade name: Petromark® Instant Gasket Black 200ml - 10421**

(Contd. of page 3)

Inhalative	cstm, long, system	7.2 mg/kg/d (mouse)
	wrks, short, system	14.5 mg/kg bw/d (rabbit)
	cstm, short, system	7.2 mg/kg bw/d (rabbit)
	wrks, long, system	25 mg/m <sup>3</sup> (mouse)
	cstm, long, system	6.3 mg/m <sup>3</sup> (mouse)
	wrks, short, system	25 mg/m <sup>3</sup> (rabbit)
	wrks, long, local	31 mg/m <sup>3</sup> (rabbit)
	cstm, long, local	5.1 mg/m <sup>3</sup> (mouse)
	cstm, short, local	5.1 mg/m <sup>3</sup> (rabbit)
	cstm, short, system	6.3 mg/m <sup>3</sup> (rabbit)
	wrks, short, local	31 mg/m <sup>3</sup> (mouse)

#### 17865-07-5 Propyltriacetoxysilan

Oral	cstm, long, system, oral	6.05 mg/kg/d (mouse)
Dermal	wrks, long, system	12.11 mg/kg/d (mouse)
	cstm, long, system	6.05 mg/kg/d (rabbit)
Inhalative	wrks, long, system	85.39 mg/m <sup>3</sup> (mouse)
	cstm, long, system	21.06 mg/m <sup>3</sup> (rabbit)

#### · PNECs

#### 29118-24-9 trans-1,3,3,3-Tetrafluoroprop-1-ene

Oral	fresh water	0.1 mg/l (daphnia)
------	-------------	--------------------

#### 4253-34-3 methylsilanetriyl triacetate

Oral	fresh water	1 mg/l (daphnia)
	sediment (fresh water)	3.4 mg/(kg dw) (daphnia)
	STP	10 mg/l (daphnia)
	soil	0.145 mg/(kg dw) (daphnia)
	sediment (marine water)	0.34 mg/(kg bw) (daphnia)
	marine water	0.1 mg/l (daphnia)
	intermittent release	10 mg/l (daphnia)

#### 17865-07-5 Propyltriacetoxysilan

Oral	fresh water	0.02441 mg/l (daphnia)
	sediment (fresh water)	0.01457 mg/(kg dw) (daphnia)
	STP	10.55 mg/l (daphnia)
	soil	0.00336 mg/(kg dw) (daphnia)
	sediment (marine water)	0.001457 mg/(kg bw) (daphnia)
	marine water	0.002441 mg/l (daphnia)

#### · Additional Occupational Exposure Limit Values for possible hazards during processing:

#### 64-19-7 acetic acid

WEL (Great Britain)	Short-term value: 50 mg/m <sup>3</sup> , 20 ppm
	Long-term value: 25 mg/m <sup>3</sup> , 10 ppm
IOELV (EU)	Short-term value: 50 mg/m <sup>3</sup> , 20 ppm
	Long-term value: 25 mg/m <sup>3</sup> , 10 ppm

· **Additional information:** The lists valid during the making were used as basis.

#### · 8.2 Exposure controls

#### · Personal protective equipment:

#### · General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working.

Wash hands before breaks and at the end of work.

(Contd. on page 5)



## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.01.2020

Version number 7

Revision: 26.09.2019

**Trade name: Petromark® Instant Gasket Black 200ml - 10421**

(Contd. of page 4)

**· Respiratory protection:**

Not necessary if room is well-ventilated.

Short term filter device:

Filter A/P2

**· Protection of hands:**

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

**· Material of gloves**Recommended thickness of the material:  $\geq 0.5$  mm

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**· Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**· Eye protection:** Goggles recommended during refilling**· Body protection:** Protective work clothing**SECTION 9: Physical and chemical properties****· 9.1 Information on basic physical and chemical properties****· General Information****· Appearance:****Form:** paste-like**Colour:** Black**· Odour:** Like aromates**· Odour threshold:** Not determined.**· pH-value:** Not determined.**· Change in condition****Melting point/freezing point:** Undetermined.**Initial boiling point and boiling range:** Not applicable, as aerosol.**· Flash point:** Not applicable, as aerosol.**· Flammability (solid, gas):** Not applicable.**· Decomposition temperature:** Not determined.**· Auto-ignition temperature:** Product is not selfigniting.**· Explosive properties:** Product does not present an explosion hazard.**· Explosion limits:****Lower:** 3.0 %**Upper:** 16 %**· Vapour pressure:** Not applicable.**· Density at 20 °C:** 1.03 g/cm<sup>3</sup>**· Relative density** Not determined.**· Vapour density** Not determined.**· Evaporation rate** Not applicable.**· Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

(Contd. on page 6)



## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.01.2020

Version number 7

Revision: 26.09.2019

**Trade name: Petromark® Instant Gasket Black 200ml - 10421**

(Contd. of page 5)

- **Partition coefficient: n-octanol/water:** Not determined.
- **Viscosity:**
  - Dynamic:** Not determined.
  - Kinematic:** Not determined.
  - VOC (EC)** 0.0 g/l
  - VOC (EU)** 0.00 %
  - VOCV (CH)** 0.00 %
- **9.2 Other information** No further relevant information available.

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Danger of bursting.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No decomposition if used according to specifications.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **LD/LC50 values relevant for classification:**

<b>4253-34-3 methylsilanetriyl triacetate</b>		
Oral	LD50	1,600 mg/kg (rat)
- **Primary irritant effect:**
- **Skin corrosion/irritation**  
No irritant effect.  
test system/specie: rabbit
- **Serious eye damage/irritation**  
No irritant effect.  
test system/specie: rabbit
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

- **12.1 Toxicity** No further relevant informations available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow product to reach ground water, water course or sewage system, even in small quantities.

(Contd. on page 7)



## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.01.2020

Version number 7

Revision: 26.09.2019

**Trade name: Petromark® Instant Gasket Black 200ml - 10421**

(Contd. of page 6)

**· 12.5 Results of PBT and vPvB assessment****· PBT:**

540-97-6 dodecamethylcyclhexasiloxane (D6)

**· vPvB:**

540-97-6 dodecamethylcyclhexasiloxane (D6)

**· 12.6 Other adverse effects** No further relevant information available.**SECTION 13: Disposal considerations****· 13.1 Waste treatment methods****· Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

**· European waste catalogue**

08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

16 05 04\* gases in pressure containers (including halons) containing hazardous substances

15 01 04 metallic packaging

**· Uncleaned packaging:****· Recommendation:** Disposal must be made according to official regulations.**SECTION 14: Transport information****· 14.1 UN-Number****· ADR, IMDG, IATA**

UN1950

**· 14.2 UN proper shipping name****· ADR**

1950 AEROSOLS

**· IMDG**

AEROSOLS

**· IATA**

AEROSOLS, non-flammable

**· 14.3 Transport hazard class(es)****· ADR****· Class**

2.5A Gases.

**· Label**

2.2

**· IMDG, IATA****· Class**

2.2

**· Label**

2.2

**· 14.4 Packing group****· ADR, IMDG, IATA**

Void

**· 14.5 Environmental hazards:****· Marine pollutant:**

No

**· 14.6 Special precautions for user**

Warning: Gases.

**· Danger code (Kemler):**

-

**· EMS Number:**

F-D,S-U

**· Stowage Code**

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1

(Contd. on page 8)





## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.01.2020

Version number 7

Revision: 26.09.2019

**Trade name: Petromark® Instant Gasket Black 200ml - 10421**

(Contd. of page 7)

· <b>Segregation Code</b>	litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADR</b> · <b>Limited quantities (LQ)</b> · <b>Excepted quantities (EQ)</b>  · <b>Transport category</b> · <b>Tunnel restriction code</b>	1L Code: E0 Not permitted as Excepted Quantity 3 E (Dangerous goods in "LQ" with more than 8 tons gross mass of LQ falls under the tunnel restriction code "E")
· <b>IMDG</b> · <b>Limited quantities (LQ)</b> · <b>Excepted quantities (EQ)</b>	1L Code: E0 Not permitted as Excepted Quantity
· <b>UN "Model Regulation":</b>	UN 1950 AEROSOLS, 2.2

\*

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **National regulations:**
- **Waterhazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.
- **Other regulations, limitations and prohibitive regulations**

#### · **Substances of very high concern (SVHC) according to REACH, Article 57**

540-97-6 | dodecamethylcyclohexasiloxane (D6)

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**  
H280 Contains gas under pressure; may explode if heated.  
H302 Harmful if swallowed.  
H314 Causes severe skin burns and eye damage.

(Contd. on page 9)

GB





## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.01.2020

Version number 7

Revision: 26.09.2019

**Trade name: Petromark® Instant Gasket Black 200ml - 10421**

(Contd. of page 8)

**· Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
ICAO: International Civil Aviation Organisation  
ctsm, long, system: general population, long-term exposure, systematic effects  
cstm, short, system: general population, acute / short-term exposure, systematic effects  
wrks, long, system: workers, long-term exposure - systemic effects  
wrks, short, system: workers, acute / short-term exposure - systemic effects  
cstm, long, local: general population, long-term exposure, local effects  
STP: sewage treatment plant  
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic compounds)  
VOC: Volatile Organic Compounds (USA, EU)  
DNEL: Derived No-Effect Level (REACH)  
PNEC: Predicted No-Effect Concentration (REACH)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
SVHC: Substances of Very High Concern  
vPvB: very Persistent and very Bioaccumulative  
Aerosol 3: Aerosols – Category 3  
Press. Gas C: Gases under pressure – Compressed gas  
Acute Tox. 4: Acute toxicity - oral – Category 4  
Skin Corr. 1B: Skin corrosion/irritation – Category 1B

**· \* Data compared to the previous version altered.**

GB