



Magna Range

Lubricating Oil

Description

Castrol Magna™ grades are a range of high quality additive-free oils possessing inherently good resistance to oxidation and good demulsification properties.

Application

Castrol Magna lubricating oils are suitable for a variety of applications such as the lubrication of bearings, spindles and, using the heavier viscosity grades, moderately loaded gearboxes. They may also be used in vacuum pumps and hydraulic systems where an 'ISO HH' fluid type is required. Magna lubricating oils are available in a range of viscosities from 320 cSt for gear lubrication down to 2 cSt for use on fine clearance high speed spindles. The Magna range is fully compatible with nitrile, silicone and fluropolymer seal materials. Magna is classified as follows: ISO 6743/4 - Type HH

Advantages

- Highly refined mineral oil makes the product suitable for applications where non-additivated oils can be used.
- Good quality mineral oil enables long service life.
- Low pour point provides trouble-free operation in cold conditions.

Typical Characteristics

Name	Method	Units	2	10	15	22	32	46	68	100	150	220	320	460
Density @ 15°C / 59°F	ISO 12185 / ASTM D4052	kg/m³	820	870	870	870	870	880	880	890	890	890	890	900
Kinematic Viscosity @ 40°C / 104°F	ISO 3104 / ASTM D445	mm²/s	2	10	15	22	32	46	68	100	150	220	320	460
Kinematic Viscosity @ 100°C / 212°F	ISO 3104 / ASTM D445	mm²/s	-	2.55	3.4	3.9	5.3	6.6	8.6	11.1	14.5	18.7	24	31.2
Viscosity Index	ISO 2909 / ASTM D2270	-	-	-	-	102	102	102	102	97	97	97	96	96
Pour Point	ISO 3016 / ASTM D97	°C/°F	-39/ -38.2	-33/ -27.4	-24/ -11.2	-18/ -0.4	-12/ 10.4	-18/-0.4	-18/ -0.4	-18/ -0.4	-18/ -0.4	-15/5	-9/15.8	-3/26.6
Flash Point - closed cup method	ISO 2719 / ASTM D93	°C/°F	85/185	140/ 284	155/ 311	160/ 320	210/ 410	222/ 431.6	220/ 428	240/ 464	255/ 491	264/ 507.2	270/ 518	264/ 507.2

Subject to usual manufacturing tolerances.

Magna Range

05 Mar 2021

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial, Technology Centre , Whitchurch Hill , Pangbourne , Reading , RG8 7QR , United Kingdom

<http://msdspdscastrol.com>