According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2611

Version Revision Date: Date of last issue: 25.03.2021 Print Date: 3.4 29.11.2022 Date of first issue: 30.03.2013 29.11.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : OKS 2611

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Cleaning agent / Cleaner, Detergent

Substance/Mixture

Recommended restrictions

on use

: Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company : OKS Spezialschmierstoffe GmbH

Ganghoferstr. 47

D-82216 Maisach-Gernlinden Tel.: +49 8142 3051 500 Fax.: +49 8142 3051 599 info@oks-germany.com

E-mail address of person : mcm@oks-germany.com

responsible for the SDS Material Compliance Management

National contact :

1.4 Emergency telephone number

Emergency telephone

number

+49 8142 3051 517 (24/7 service)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Aerosols, Category 1 H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Specific target organ toxicity - single exposure, Category 3, Central nervous

system

H336: May cause drowsiness or dizziness.



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2611

Version Revision Date: Date of last issue: 25.03.2021 Print Date: 3.4 29.11.2022 Date of first issue: 30.03.2013 29.11.2022

Aspiration hazard, Category 1 H304: May be fatal if swallowed and enters

airways.

Long-term (chronic) aquatic hazard,

Category 3

H412: Harmful to aquatic life with long lasting

effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms :







Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H304 May be fatal if swallowed and enters

airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H412 Harmful to aquatic life with long lasting

effects.

Precautionary statements : **Prevention:**

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other

ignition source.

P251 Do not pierce or burn, even after use.

Response:

P301 + P310 IF SWALLOWED: Immediately call a

POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

Storage:

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

propan-2-ol

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2611

VersionRevision Date:Date of last issue: 25.03.2021Print Date:3.429.11.2022Date of first issue: 30.03.201329.11.2022

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

acetone

Additional Labelling

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Active substance with propellant

Solvent mixture

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	specific concentration limit M-Factor Notes Acute toxicity estimate	Concentration (% w/w)
propan-2-ol	67-63-0 200-661-7 603-117-00-0	Flam. Liq.2; H225 Eye Irrit.2; H319 STOT SE3; H336		>= 20 - < 30
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	927-241-2	Flam. Liq.3; H226 STOT SE3; H336 Asp. Tox.1; H304 Aquatic Chronic3; H412; EUH066		>= 25 - < 30
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	921-024-6	Flam. Liq.2; H225 Skin Irrit.2; H315 STOT SE3; H336 Asp. Tox.1; H304 Aquatic Chronic2; H411		>= 20 - < 25
acetone	67-64-1 200-662-2	Flam. Liq.2; H225 Eye Irrit.2; H319		>= 10 - < 20



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2611

VersionRevision Date:Date of last issue: 25.03.2021Print Date:3.429.11.2022Date of first issue: 30.03.201329.11.2022

	606-001-00-8	STOT SE3; H336	
Substances with a wor	xplace exposure limit:		
carbon dioxide	124-38-9 204-696-9	Press. GasCompr. Gas; H280	>= 1 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

If inhaled : Call a physician or poison control centre immediately.

Remove person to fresh air. If signs/symptoms continue, get

medical attention.

Keep patient warm and at rest.

If unconscious, place in recovery position and seek medical

advice.

Keep respiratory tract clear.

If breathing is irregular or stopped, administer artificial

respiration.

In case of skin contact : Take off all contaminated clothing immediately.

Get medical attention immediately if irritation develops and

persists.

Wash clothing before reuse.

Thoroughly clean shoes before reuse. Wash off immediately with plenty of water.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 10 minutes. Seek medical advice.

If swallowed : Move the victim to fresh air.

If accidentally swallowed obtain immediate medical attention.

Keep respiratory tract clear. Do NOT induce vomiting. Rinse mouth with water.

Aspiration hazard if swallowed - can enter lungs and cause

damage.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Inhalation may provoke the following symptoms:

Unconsciousness

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2611

Version Revision Date: Date of last issue: 25.03.2021 Print Date: 3.4 29.11.2022 Date of first issue: 30.03.2013 29.11.2022

Dizziness Drowsiness Headache Nausea Tiredness

Skin contact may provoke the following symptoms:

Erythema

Aspiration may cause pulmonary oedema and pneumonitis.

Risks : Central nervous system depression

Risk of product entering the lungs on vomiting after ingestion.

Health injuries may be delayed.

Causes skin irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : ABC powder

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Fire Hazard

Do not let product enter drains.

Contains gas under pressure; may explode if heated. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Hazardous combustion

products

: Carbon oxides

5.3 Advice for firefighters

Special protective equipment :

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment. Exposure to decomposition products may be a hazard to health.

Further information : Standard procedure for chemical fires.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains. Cool containers/tanks with water spray.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2611

Version Revision Date: Date of last issue: 25.03.2021 Print Date: 3.4 29.11.2022 Date of first issue: 30.03.2013 29.11.2022

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.

Ensure adequate ventilation. Remove all sources of ignition. Do not breathe vapours or spray mist.

Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Refer to protective measures listed in sections 7 and 8. Only qualified personnel equipped with suitable protective

equipment may intervene.

6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible

absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

Non-sparking tools should be used.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not use in areas without adequate ventilation.

Do not breathe vapours or spray mist.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin and eyes. For personal protection see section 8.

Keep away from fire, sparks and heated surfaces. Smoking, eating and drinking should be prohibited in the

application area.

Wash hands and face before breaks and immediately after

handling the product.

Do not get in eyes or mouth or on skin.

Do not get on skin or clothing.

Do not ingest.

Do not use sparking tools.



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2611

Version Revision Date: Date of last issue: 25.03.2021 Print Date: 3.4 29.11.2022 Date of first issue: 30.03.2013 29.11.2022

These safety instructions also apply to empty packaging which

may still contain product residues.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or

burn, even after use.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after

handling.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in accordance with the particular

national regulations.

7.3 Specific end use(s)

Specific use(s) : Specific instructions for handling, not required.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
propan-2-ol	67-63-0	STEL	500 ppm	GB EH40GB
			1,250 mg/m3	EH40 (2006-09-01)
		TWA	400 ppm	GB EH40GB
			999 mg/m3	EH40
acetone	67-64-1	TWA	500 ppm	(2006-09-01) GB EH40GB
doctoric	07 04 1	1 4474	1,210 mg/m3	EH40
			,	(2005-04-06)
		STEL	1,500 ppm	GB EH40GB
			3,620 mg/m3	EH40
		TWA	500 nnm	(2005-04-06) 2000/39/EC2
		IVVA	500 ppm 1,210 mg/m3	000/39/EC2
			1,210g/0	(2000-06-16)
	Further info	Further information: Indicative		
carbon dioxide	124-38-9	TWA	5,000 ppm	GB EH40GB
			9,150 mg/m3	EH40
				(2005-04-06)
		STEL	15,000 ppm	GB EH40GB

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2611

VersionRevision Date:Date of last issue: 25.03.2021Print Date:3.429.11.2022Date of first issue: 30.03.201329.11.2022

		27,400 mg/m3	EH40 (2005-04-06)
	TWA	5,000 ppm 9,000 mg/m3	2006/15/EC2 006/15/EC (2006-02-09)
Further information: Indicative			

Derived No Effect Level (DNEL):

Substance name	End Use	Exposure routes	Potential health effects	Value
propan-2-ol	Workers	Inhalation	Long-term systemic effects	500 mg/m3
	Workers	Skin contact	Long-term systemic effects	888 mg/kg
Hydrocarbons, C6- C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Workers	Skin contact	Long-term systemic effects	773 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	2035 mg/m3
acetone	Workers	Inhalation	Long-term systemic effects	1210 mg/m3
	Workers	Skin contact	Long-term systemic effects	186 mg/kg

Predicted No Effect Concentration (PNEC):

Substance name	Environmental Compartment	Value
acetone	Fresh water	10.6 mg/l
	Marine water	1.06 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	30.4 mg/kg
	Marine sediment	3.04 mg/kg
	Soil	29.5 mg/kg

8.2 Exposure controls

Engineering measures

Use only in an area equipped with explosion proof exhaust ventilation. Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

Eye protection : Safety glasses with side-shields

Hand protection

Material : butyl-rubber
Break through time : > 10 min
Protective index : Class 1

Remarks : Wear protective gloves. The break through time depends

amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2611

Version Revision Date: Date of last issue: 25.03.2021 Print Date: 3.4 29.11.2022 Date of first issue: 30.03.2013 29.11.2022

case.

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Recommended Filter type:

Organic gas and low boiling vapour type (AX)

Protective measures : The type of protective equipment must be selected according

to the concentration and amount of the dangerous substance

at the specific workplace.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : aerosol

Colour : colourless

Odour : solvent-like

Odour Threshold : No data available

pH : Not applicable

substance/mixture is non-soluble (in water)

Melting point/range : No data available

Boiling point/boiling range : 56 °C (1,013 hPa)

Flash point : -18 °C

Method: Abel-Pensky

Evaporation rate : No data available

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper

flammability limit

: 13 %(V)



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2611

Version **Revision Date:** Date of last issue: 25.03.2021 Print Date: 3.4 29.11.2022 Date of first issue: 30.03.2013 29.11.2022

Lower explosion limit / Lower : 0.6 %(V)

flammability limit

Vapour pressure : 233 hPa (20 °C)

Relative vapour density : No data available

: 0.7533 (20 °C) Relative density

> Reference substance: Water The value is calculated

Density 0.75 g/cm3

(20 °C)

Bulk density No data available

Solubility(ies)

insoluble Water solubility

Solubility in other solvents No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : No data available

Decomposition temperature No data available

Viscosity

Viscosity, dynamic No data available

Viscosity, kinematic < 20.5 mm2/s (40 °C)

Explosive properties Not explosive

Oxidizing properties No data available

9.2 Other information

Sublimation point No data available

Metal corrosion rate Not corrosive to metals

Self-ignition not auto-flammable

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2611

Version Revision Date: Date of last issue: 25.03.2021 Print Date: 3.4 29.11.2022 Date of first issue: 30.03.2013 29.11.2022

SECTION 10: Stability and reactivity

10.1 Reactivity

No hazards to be specially mentioned.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

Strong sunlight for prolonged periods.

Risk of receptacle bursting.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product:

Acute oral toxicity : Remarks: Effects due to ingestion may include:

Symptoms: Central nervous system depression

Acute inhalation toxicity : Remarks: Respiration of solvent vapour may cause dizziness.

Harmful by inhalation.

Symptoms: Inhalation may provoke the following symptoms:, Respiratory disorder, Dizziness, Drowsiness, Vomiting, Fatigue, Vertigo, Central nervous system depression

Acute dermal toxicity : Symptoms: Redness, Local irritation

Components:

propan-2-ol:

Acute oral toxicity : LD50 Oral (Rat): 5,840 mg/kg

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2611

Version Revision Date: Date of last issue: 25.03.2021 Print Date: 3.4 29.11.2022 Date of first issue: 30.03.2013 29.11.2022

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Acute oral toxicity : LD50 (Rat): > 5,840 mg/kg

Assessment: The substance or mixture has no acute oral

toxicity

Acute inhalation toxicity : LC50 (Rat): > 25.2 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Assessment: The substance or mixture has no acute

inhalation toxicity

Acute dermal toxicity : LD50 (Rat): > 2.8 g/kg

Assessment: The substance or mixture has no acute dermal

toxicity

acetone:

Acute oral toxicity : LD50 Oral (Rat): 5,800 mg/kg

Skin corrosion/irritation

Product:

Remarks : Irritating to skin.

Components:

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Result : Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit

Assessment : Irritating to skin.

Method : OECD Test Guideline 404

Result : Irritating to skin.

Serious eye damage/eye irritation

Product:

Remarks : Irritating to eyes.

Components:

propan-2-ol:

Result : Irritating to eyes.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2611

Version Revision Date: Date of last issue: 25.03.2021 Print Date: 3.4 29.11.2022 Date of first issue: 30.03.2013 29.11.2022

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit

Assessment : No eye irritation Result : No eye irritation

acetone:

Species : Rabbit Result : Eye irritation

Respiratory or skin sensitisation

Product:

Remarks : This information is not available.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Test Type : Maximisation Test

Exposure routes : Dermal Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Did not cause sensitisation on laboratory animals.

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Test system: Rodent cell line Method: OECD Test Guideline 473

Result: negative

Carcinogenicity

Product:

Remarks : No data available

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2611

Version Revision Date: Date of last issue: 25.03.2021 Print Date: 3.4 29.11.2022 Date of first issue: 30.03.2013 29.11.2022

Effects on foetal : Remarks: No data available

development

STOT - single exposure

Components:

propan-2-ol:

Assessment : May cause drowsiness or dizziness.

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Exposure routes : Inhalation

Assessment : May cause drowsiness or dizziness.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Assessment : May cause drowsiness or dizziness.

acetone:

Exposure routes : Inhalation

Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Exposure routes : inhalation (vapour)

Assessment : No significant health effects observed in animals at

concentrations of 1 mg/l/6h/d or less.

Repeated dose toxicity

Product:

Remarks : This information is not available.

Aspiration toxicity

Product:

May be fatal if swallowed and enters airways.

May be fatal if swallowed and enters airways.

Components:

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

May be fatal if swallowed and enters airways.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2611

Version **Revision Date:** Date of last issue: 25.03.2021 Print Date: 29.11.2022 Date of first issue: 30.03.2013 29.11.2022 3.4

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks Risks of irreversible effects after a single exposure.

Ingestion causes irritation of upper respiratory system and

gastrointestinal disturbance.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: Harmful to aquatic organisms, may cause long-term

adverse effects in the aquatic environment.

Toxicity to daphnia and other : Remarks: No data available

aquatic invertebrates

Toxicity to algae/aquatic

plants

Remarks: No data available

Toxicity to microorganisms

Remarks: No data available

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Physico-chemical

removability

Remarks: No data available

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: This mixture contains no substance considered to

be persistent, bioaccumulating and toxic (PBT).

This mixture contains no substance considered to be very

persistent and very bioaccumulating (vPvB).

12.4 Mobility in soil

Product:

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2611

Version Revision Date: Date of last issue: 25.03.2021 Print Date: 3.4 29.11.2022 Date of first issue: 30.03.2013 29.11.2022

Mobility : Remarks: No data available

Distribution among

environmental compartments

Remarks: No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Other adverse effects

Product:

potential

Endocrine disrupting : The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Additional ecological

information

: Harmful to aquatic life with long lasting effects.

Global warming potential

The Fifth Assessment Report of the United Nations Intergovernmental Panel on Climate Change (IPCC)

Components:

carbon dioxide:

20-year global warming potential: 1 100-year global warming potential: 1

Further information: No single lifetime can be given. The impulse response function for CO2 from

Joos et al. (2013) has been used. See also Supplementary Material Section 8.SM.11.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.

Dispose of as hazardous waste in compliance with local and

national regulations.

Waste codes should be assigned by the user based on the

application for which the product was used.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2611

Version Revision Date: Date of last issue: 25.03.2021 Print Date: 3.4 29.11.2022 Date of first issue: 30.03.2013 29.11.2022

the unused product.

Offer empty spray cans to an established disposal company. Pressurized container: Do not pierce or burn, even after use.

The following Waste Codes are only suggestions:

Waste Code : unused product, packagings not completely emptied

16 05 04*, gases in pressure containers (including halons)

containing hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 1950
RID : UN 1950
IMDG : UN 1950
IATA : UN 1950

14.2 UN proper shipping name

ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS

IATA : Aerosols, flammable

14.3 Transport hazard class(es)

ADR : 2
RID : 2
IMDG : 2.1
IATA : 2.1

14.4 Packing group

ADR

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1 Tunnel restriction code : (D)

RID

Packing group : Not assigned by regulation

Classification Code : 5F Hazard Identification Number : 23 Labels : 2.1

IMDG



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2611

Version **Revision Date:** Date of last issue: 25.03.2021 Print Date: 29.11.2022 Date of first issue: 30.03.2013 29.11.2022 3.4

Packing group Not assigned by regulation

Labels 2.1 **EmS Code** F-D, S-U

IATA (Cargo)

Packing instruction (cargo : 203

aircraft)

Packing instruction (LQ) Y203

Packing group Not assigned by regulation

Flammable Gas Labels

IATA (Passenger)

Packing instruction 203

(passenger aircraft)

Packing instruction (LQ) Y203

Packing group Not assigned by regulation

Labels Flammable Gas

14.5 Environmental hazards

ADR

Environmentally hazardous : no

Environmentally hazardous no

IMDG

Marine pollutant no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).

(EU SVHC)

This product does not contain substances of very high concern (Regulation (EC) No

1907/2006 (REACH), Article 57).

REACH - List of substances subject to authorisation

(Annex XIV)

(EU. REACH-Annex XIV)

Not applicable



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



Not applicable

Not applicable

Not applicable

Not applicable

Not applicable

acetone

(ANNEX II)

OKS 2611

Version Revision Date: Date of last issue: 25.03.2021 Print Date: 3.4 29.11.2022 Date of first issue: 30.03.2013 29.11.2022

Regulation (EC) No 1005/2009 on substances that

deplete the ozone layer

(EC 1005/2009)

Regulation (EU) 2019/1021 on persistent organic

pollutants (recast)

(EU POP)

Regulation (EC) No 649/2012 of the European

Parliament and the Council concerning the export and

import of dangerous chemicals

(EU PIC)

UK REACH List of substances subject to authorisation

(Annex XIV)

(UK. REACH Annex XIV)

GB Export and import of hazardous chemicals - Prior

Informed Consent (PIC) Regulation

(GB PIC)

Regulation (EU) 2019/1148 on the marketing and use of : Listed

explosives precursors

This product is regulated by Regulation (EU) 2019/1148:

all suspicious transactions, and significant

disappearances and thefts should be reported to the

relevant national contact point. Please see

https://ec.europa.eu/home-affairs/sites/

homeaffairs/files/what-we-do/policies/crisis-and-

terrorism/explosives/explosives-

precursors/docs/list_of_competent_authorities_and_nati

onal_contact_points_en.pdf

according to Detergents : Ingredients

Regulation EC 648/2004 15 - < 30%: Aliphatic hydrocarbons

15.2 Chemical safety assessment

This information is not available.

SECTION 16: Other information

Full text of R-Phrases

Note P : The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains

less than 0,1 % w/w benzene (Einecs No 200-753-7), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes.

Where the substance is not classified as a carcinogen or

a brand of
FREUDENBERG

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2611

VersionRevision Date:Date of last issue: 25.03.2021Print Date:3.429.11.2022Date of first issue: 30.03.201329.11.2022

mutagen, at least the precautionary statements (P102-)P260-

P262-P301 + P310-P331 shall apply.

Full text of H-Statements

EUH066 : Repeated exposure may cause skin dryness or cracking.

H225 : Highly flammable liquid and vapour. H226 : Flammable liquid and vapour.

H280 : Contains gas under pressure; may explode if heated.

H304 : May be fatal if swallowed and enters airways.

H315 : Causes skin irritation.

H319 : Causes serious eye irritation.
H336 : May cause drowsiness or dizziness.

H411 : Toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Note P : The harmonised classification as a carcinogen or mutagen

applies unless it can be shown that the substance contains less than 0,1 % w/w benzene (Einecs No 200-753-7), in which

case a classification in accordance with Title II of this

Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P260-

P262-P301 + P310-P331 shall apply.

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values
Europe. Indicative occupational exposure limit values

2006/15/EC : Europe. Indicative occupational exposure limit GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

2000/39/EC / TWA : Limit Value - eight hours 2006/15/EC / TWA : Limit Value - eight hours

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2611

VersionRevision Date:Date of last issue: 25.03.2021Print Date:3.429.11.2022Date of first issue: 30.03.201329.11.2022

International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG -United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Classification of the mixture:

Classification procedure:

Aerosol 1	H222, H229	Based on product data or assessment
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
STOT SE 3	H336	Calculation method
Asp. Tox. 1	H304	Based on product data or assessment
Aquatic Chronic 3	H412	Calculation method

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.