according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



STRUCTOVIS FHD Spray

Version Revision Date: Date of last issue: 05.01.2021 Print Date: 1.8 08.09.2021 Date of first issue: 19.06.2017 09.09.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : STRUCTOVIS FHD Spray

Article-No. : 081340

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Lubricant spray

stance/Mixture

Recommended restrictions

on use

Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company : Klüber Lubrication München

Geisenhausenerstr. 7 81379 München Deutschland

Tel: +49 (0) 89 7876 0 Fax: +49 (0) 89 7876 333

info@klueber.com

E-mail address of person : mcm@klueber.com

responsible for the SDS Material Compliance Management

National contact : Klüber Lubrication Deutschland

Geisenhausenerstraße 7

81379 München Deutschland Tel.: +49 89 7876 0 Fax: +49 89 7876 565

customer.service.de@klueber.com

www.klueber.com

1.4 Emergency telephone number

Emergency telephone num- : +49 89 7876 700 (24 hrs)

ber

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.

according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



STRUCTOVIS FHD Spray

Version Revision Date: Date of last issue: 05.01.2021 Print Date: 1.8 08.09.2021 Date of first issue: 19.06.2017 09.09.2021

H229: Pressurised container: May burst if heated.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other

ignition source.

P251 Do not pierce or burn, even after use.

Storage:

P410 + P412 Protect from sunlight. Do not expose to tem-

peratures exceeding 50 °C/ 122 °F.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Mineral oil.

Propellant

Components

| •••••••••••••••••••••••••••••••••••••• | | | | |
|--|---------|----------------|------------------|---------------|
| Chemical name | CAS-No. | Classification | specific concen- | Concentration |
| | FC-No | | tration limit | (% w/w) |



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



STRUCTOVIS FHD Spray

Version Revision Date: Date of last issue: 05.01.2021 Print Date: 1.8 08.09.2021 Date of first issue: 19.06.2017 09.09.2021

| | | | M Footor | |
|--|-----------------------------------|----------------------|-------------------|--------------|
| | Index-No. | | M-Factor Notes | |
| | Registration number | | Acute toxicity | |
| | Trogiotration nambor | | estimate | |
| Substances with a work | place exposure limit : | | ooato | |
| isobutane | 75-28-5 200-857-2 | Flam. Gas1A; H220 | | >= 30 - < 50 |
| | 200 007 2 | Press. GasCompr. | Note U (table | |
| | 601-004-00-0 01-2119485395-27- | Gas; H280 | 3.1), Note C | |
| | XXXX | | | |
| residual oils (petrole- | 64742-57-0 | Not classified | | >= 20 - < 30 |
| um), hydrotreated | 265-160-8 | | Niete I | |
| | 649-470-00-4 | | Note L | |
| | 01-2119489287-22- | | | |
| | XXXX | | | |
| | | | | |
| Distillates (petroleum), | 64742-54-7 | Not classified | | >= 10 - < 20 |
| hydrotreated heavy paraffinic; Baseoil — | 265-157-1 | | Note L | |
| unspecified | 649-467-00-8 | | NOIC L | |
| | 01-2119484627-25- | | | |
| | XXXX | | | |
| White mineral oil (no | 8042-47-5 | Not classified | | >= 10 - < 20 |
| White mineral oil (petroleum) | 232-455-8 | Not classified | | >= 10 - < 20 |
| li oloum) | 202 400 0 | | | |
| | 01-2119487078-27- | | | |
| | XXXX | | | |
| propane | 74-98-6 | Flam. Gas1A; | | >= 1 - < 10 |
| p. 500110 | 200-827-9 | H220 | | 7-1 10 |
| | | Press. GasCompr. | Note U (table | |
| | 601-003-00-5 | Gas; H280 | 3.1) | |
| | 01-2119486944-21- XXXX | | | |
| | | | | |
| butane | 106-97-8 | Flam. Gas1A; | | >= 1 - < 10 |
| | 203-448-7 | H220 | | |
| | 004 004 00 0 | Press. GasCompr. | Note U (table | |
| | 601-004-00-0 01-2119474691-32- | Gas; H280 | 3.1), Note C | |
| | XXXX | | | |
| | | | | |

For explanation of abbreviations see section 16.



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



STRUCTOVIS FHD Spray

Version Revision Date: Date of last issue: 05.01.2021 Print Date: 1.8 08.09.2021 Date of first issue: 19.06.2017 09.09.2021

SECTION 4: First aid measures

4.1 Description of first aid measures

If inhaled : Remove person to fresh air. If signs/symptoms continue, get

medical attention.

Keep patient warm and at rest.

If unconscious, place in recovery position and seek medical

advice.

Keep respiratory tract clear.

If breathing is irregular or stopped, administer artificial respira-

tion

In case of skin contact : Remove contaminated clothing. If irritation develops, get med-

ical attention.

Wash off with soap and plenty of water.

Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 10 minutes.

If eye irritation persists, consult a specialist.

If swallowed : Move the victim to fresh air.

Keep respiratory tract clear. Do NOT induce vomiting. Rinse mouth with water.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Inhalation may provoke the following symptoms:

Unconsciousness

Dizziness Drowsiness Headache Nausea Tiredness

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : ABC powder

Unsuitable extinguishing

media

: High volume water jet



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



STRUCTOVIS FHD Spray

Version Revision Date: Date of last issue: 05.01.2021 Print Date: 08.09.2021 Date of first issue: 19.06.2017 09.09.2021 1.8

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Fire Hazard

Do not let product enter drains.

Contains gas under pressure; may explode if heated.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

Hazardous combustion prod- : Carbon oxides

ucts

5.3 Advice for firefighters

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. Exposure to decomposi-

tion products may be a hazard to health.

Further information Standard procedure for chemical fires.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains. Cool containers/tanks with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe areas. Personal precautions

Ensure adequate ventilation. Remove all sources of ignition.

Refer to protective measures listed in sections 7 and 8. Only qualified personnel equipped with suitable protective

equipment may intervene.

6.2 Environmental precautions

Environmental precautions Try to prevent the material from entering drains or water

courses.

Prevent further leakage or spillage if safe to do so. Local authorities should be advised if significant spillages

cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up Contain spillage, and then collect with non-combustible ab-

sorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

Keep in suitable, closed containers for disposal.

Non-sparking tools should be used.

6.4 Reference to other sections

For personal protection see section 8.



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



STRUCTOVIS FHD Spray

VersionRevision Date:Date of last issue: 05.01.2021Print Date:1.808.09.2021Date of first issue: 19.06.201709.09.2021

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not use in areas without adequate ventilation.

Do not breathe vapours or spray mist.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin and eyes. For personal protection see section 8.

Keep away from fire, sparks and heated surfaces.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Wash hands and face before breaks and immediately after

handling the product.

Do not ingest.

Do not use sparking tools.

These safety instructions also apply to empty packaging which

may still contain product residues.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn,

even after use.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after

handling.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in accordance with the particular na-

tional regulations.

Storage class (TRGS 510) : 2B, Aerosol cans and lighters

7.3 Specific end use(s)

Specific use(s) : Specific instructions for handling, not required.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Basis |
|------------|---------|-------------------------------|--------------------------|----------------|
| isobutane | 75-28-5 | AGW | 1.000 ppm 2.400 mg/m3 | DE TRGS 900 |



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



STRUCTOVIS FHD Spray

VersionRevision Date:Date of last issue: 05.01.2021Print Date:1.808.09.2021Date of first issue: 19.06.201709.09.2021

| | | | | (2006-01-01) | | |
|-----------------------|--|--|-------------|----------------|--|--|
| | Peak-limit: excursion factor (category): 4;(II) | | | | | |
| residual oils (petro- | 64742-57-0 | AGW (Vapour | 5 mg/m3 | DE TRGS | | |
| leum), hydrotreat- | | and aerosols) | | 900 | | |
| ed | | | | (2018-06-07) | | |
| | Peak-limit: excursion factor (category): 4;(II) | | | | | |
| | Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child | | | | | |
| | | | | | | |
| Distillates (petrole- | 64742-54-7 | AGW (Vapour | 5 mg/m3 | DE TRGS | | |
| um), hydrotreated | | and aerosols) | | 900 | | |
| heavy paraffinic; | | | | (2018-06-07) | | |
| Baseoil — un- | | | | | | |
| specified | Dool limit or | Deal Part and a series for the foreign A (III) | | | | |
| | Peak-limit: excursion factor (category): 4;(II) | | | | | |
| | Further information: When there is compliance with the OEL and biological | | | | | |
| White mineral oil | tolerance values, there is no risk of harming the unborn child | | | | | |
| (petroleum) | 8042-47-5 | AGW (Alveolate fraction) | 5 mg/m3 | DE TRGS 900 | | |
| (petroleum) | | maction) | | (2015-11-06) | | |
| | Peak-limit: excursion factor (category): 4;(II) | | | | | |
| | Further information: When there is compliance with the OEL and biological | | | | | |
| | tolerance values, there is no risk of harming the unborn child | | | | | |
| propane | 74-98-6 | AGW | 1.000 ppm | DE TRGS | | |
| F F | | | 1.800 mg/m3 | 900 | | |
| | | | | (2006-01-01) | | |
| | Peak-limit: excursion factor (category): 4;(II) | | | | | |
| butane | 106-97-8 | AGW | 1.000 ppm | DE TRGS | | |
| | | | 2.400 mg/m3 | 900 | | |
| | | | | (2006-01-01) | | |
| | Peak-limit: excursion factor (category): 4;(II) | | | | | |

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Substance name | End Use | Exposure routes | Potential health effects | Value |
|--|---------|-----------------|----------------------------|-----------|
| residual oils (petrole- um), hydrotreated | Workers | Inhalation | Long-term systemic effects | 2,7 mg/m3 |
| | Workers | Inhalation | Acute systemic effects | 5,6 mg/m3 |
| | Workers | Skin contact | Long-term systemic effects | 1 mg/kg |
| Distillates (petrole- um), hydrotreated heavy paraffinic; Baseoil — unspecified | Workers | Inhalation | Long-term local effects | 5,6 mg/m3 |
| White mineral oil (petroleum) | Workers | Inhalation | Long-term systemic effects | 160 mg/m3 |
| | Workers | Skin contact | Long-term systemic effects | 220 mg/kg |

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

| Substance name | Environmental Compartment | Value |
|------------------------------|---------------------------|------------|
| Distillates (petroleum), hy- | Oral | 9,33 mg/kg |



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



STRUCTOVIS FHD Spray

Version Revision Date: Date of last issue: 05.01.2021 Print Date: 1.8 08.09.2021 Date of first issue: 19.06.2017 09.09.2021

drotreated heavy paraffinic;
Baseoil — unspecified

8.2 Exposure controls

Engineering measures

Use only in an area equipped with explosion proof exhaust ventilation. Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

Eye protection : Safety glasses with side-shields

Hand protection

Material : Nitrile rubber
Break through time : > 10 min
Protective index : Class 1

Remarks : For prolonged or repeated contact use protective gloves. The

break through time depends amongst other things on the material, the thickness and the type of glove and therefore

has to be measured for each case.

The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374

derived from it.

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Short term only

Filter type : Filter type A-P

Protective measures : The type of protective equipment must be selected according

to the concentration and amount of the dangerous substance

at the specific workplace.

Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the spe-

cific work-place.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : aerosol

Colour : brown

Odour : characteristic

Odour Threshold : No data available

according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



STRUCTOVIS FHD Spray

Version Revision Date: Date of last issue: 05.01.2021 Print Date: 1.8 08.09.2021 Date of first issue: 19.06.2017 09.09.2021

Values refer to the propellant:

Melting point/range : No data available

Boiling point/boiling range : < -10 °C

Flammability : No data available

Upper explosion limit / Upper

flammability limit

11,2 %(V)

Lower explosion limit / Lower

flammability limit

1,5 %(V)

Flash point : -60 °C

Method: closed cup

Auto-ignition temperature : > 350 °C

Decomposition temperature

Decomposition tempera-

ture

No data available

pH : Not applicable

substance/mixture is non-soluble (in water)

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Solubility(ies)

Water solubility : < 0,1 g/l insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Vapour pressure : 2.700 hPa (20 °C)

Relative density : 0,890 (20 °C)

Reference substance: Water The value is calculated

Density : 0,89 g/cm3

(20 °C)

see user defined free text

Bulk density : No data available

according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



STRUCTOVIS FHD Spray

Version Revision Date: Date of last issue: 05.01.2021 Print Date: 1.8 08.09.2021 Date of first issue: 19.06.2017 09.09.2021

Relative vapour density : No data available

9.2 Other information

Explosives : Not explosive

Oxidizing properties : No data available

Self-ignition : No data available

Evaporation rate : No data available

Sublimation point : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No hazards to be specially mentioned.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product:

Acute oral toxicity : Remarks: This information is not available.

Acute inhalation toxicity : Symptoms: Inhalation may provoke the following symptoms:,

Respiratory disorder

Acute dermal toxicity : Remarks: This information is not available.

according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



STRUCTOVIS FHD Spray

VersionRevision Date:Date of last issue: 05.01.2021Print Date:1.808.09.2021Date of first issue: 19.06.201709.09.2021

Components:

isobutane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l

Exposure time: 4 h
Test atmosphere: gas

residual oils (petroleum), hydrotreated:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 5.000 mg/kg

Method: OECD Test Guideline 402

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Method: OECD Test Guideline 401

GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 5,53 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Method: OECD Test Guideline 402

White mineral oil (petroleum):

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Method: OECD Test Guideline 401

GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

GLP: ves

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg

Method: OECD Test Guideline 402

GLP: yes

Assessment: The substance or mixture has no acute dermal

toxicity

butane:



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



STRUCTOVIS FHD Spray

Version Revision Date: Date of last issue: 05.01.2021 Print Date: 1.8 08.09.2021 Date of first issue: 19.06.2017 09.09.2021

Acute inhalation toxicity : LC50 (Rat): 658 mg/l

Exposure time: 4 h Test atmosphere: gas

Skin corrosion/irritation

Product:

Remarks : This information is not available.

Components:

residual oils (petroleum), hydrotreated:

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404

Result : No skin irritation

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404

Result : No skin irritation

GLP : yes

White mineral oil (petroleum):

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404

Result : No skin irritation

GLP : yes

Serious eye damage/eye irritation

Product:

Remarks : Contact with eyes may cause irritation.

Components:

residual oils (petroleum), hydrotreated:

Species : Rabbit

Assessment : No eye irritation

Method : OECD Test Guideline 405

Result : No eye irritation

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Species : Rabbit

Assessment : No eye irritation

Method : OECD Test Guideline 405

according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



STRUCTOVIS FHD Spray

Version Revision Date: Date of last issue: 05.01.2021 Print Date: 1.8 08.09.2021 Date of first issue: 19.06.2017 09.09.2021

Result : No eye irritation

GLP : yes

White mineral oil (petroleum):

Species : Rabbit

Assessment : No eye irritation

Method : OECD Test Guideline 405

Result : No eye irritation

GLP : yes

Respiratory or skin sensitisation

Product:

Remarks : This information is not available.

Components:

residual oils (petroleum), hydrotreated:

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

Assessment : Does not cause respiratory sensitisation.
Result : Does not cause respiratory sensitisation.

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

GLP : yes

White mineral oil (petroleum):

Test Type : Maximisation Test

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

GLP : yes

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



STRUCTOVIS FHD Spray

Version Revision Date: Date of last issue: 05.01.2021 Print Date: 1.8 08.09.2021 Date of first issue: 19.06.2017 09.09.2021

Components:

White mineral oil (petroleum):

Genotoxicity in vitro : Test Type: Ames test

Method: Mutagenicity (Salmonella typhimurium - reverse mu-

tation assay) Result: negative GLP: yes

Germ cell mutagenicity- As-

sessment

Tests on bacterial or mammalian cell cultures did not show

mutagenic effects.

Carcinogenicity

Product:

Remarks : No data available

Components:

residual oils (petroleum), hydrotreated:

Carcinogenicity - Assess-

ment

: Not classifiable as a human carcinogen.

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Carcinogenicity - Assess-

ment

: Not classifiable as a human carcinogen.

White mineral oil (petroleum):

Carcinogenicity - Assess-

ment

: No evidence of carcinogenicity in animal studies.

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Effects on foetal develop-

ment

Remarks: No data available

Components:

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Reproductive toxicity - As- : - Fertility -

sessment No toxicity to reproduction

White mineral oil (petroleum):

according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



STRUCTOVIS FHD Spray

Version Revision Date: Date of last issue: 05.01.2021 Print Date: 1.8 08.09.2021 Date of first issue: 19.06.2017 09.09.2021

Reproductive toxicity - As-

sessment

: - Fertility -

No toxicity to reproduction

- Teratogenicity -

No effects on or via lactation

STOT - single exposure

Components:

White mineral oil (petroleum):

Assessment : The substance or mixture is not classified as specific target

organ toxicant, single exposure.

STOT - repeated exposure

Components:

White mineral oil (petroleum):

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

Repeated dose toxicity

Product:

Remarks : This information is not available.

Components:

White mineral oil (petroleum):

NOAEL : 1.800 mg/kg

Exposure time : 90 d

Aspiration toxicity

Product:

This information is not available.

Components:

residual oils (petroleum), hydrotreated:

No aspiration toxicity classification

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

No aspiration toxicity classification

White mineral oil (petroleum):

No aspiration toxicity classification



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



STRUCTOVIS FHD Spray

VersionRevision Date:Date of last issue: 05.01.2021Print Date:1.808.09.2021Date of first issue: 19.06.201709.09.2021

Further information

Product:

Remarks : Information given is based on data on the components and

the toxicology of similar products.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: No data available

Toxicity to algae/aquatic

plants

Remarks: No data available

Toxicity to microorganisms

Remarks: No data available

Components:

residual oils (petroleum), hydrotreated:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h Test Type: static test

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10.000 mg/l

Exposure time: 48 h Test Type: Immobilization

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h Test Type: static test

Method: OECD Test Guideline 203

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10.000 mg/l

Exposure time: 48 h
Test Type: Immobilization

Method: OECD Test Guideline 202

GLP: yes

Toxicity to daphnia and other : aquatic invertebrates (Chron-

NOEC: 10 mg/l Exposure time: 21 d

a brand of

FREUDENBERG

according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



STRUCTOVIS FHD Spray

Version Revision Date: Date of last issue: 05.01.2021 Print Date: 1.8 08.09.2021 Date of first issue: 19.06.2017 09.09.2021

ic toxicity) Species: Daphnia magna (Water flea)

Test Type: semi-static test

Method: OECD Test Guideline 211

GLP: yes

White mineral oil (petroleum):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l

Exposure time: 96 h Test Type: static test

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia (water flea)): > 100 mg/l

Exposure time: 48 h
Test Type: Immobilization

Method: OECD Test Guideline 202

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

NOEC: >= 1.000 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Physico-chemical removabil- :

ity

Remarks: No data available

Components:

residual oils (petroleum), hydrotreated:

Biodegradability : Result: Not rapidly biodegradable

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Biodegradability : Test Type: aerobic

Inoculum: activated sludge Result: Not rapidly biodegradable

Biodegradation: 3 % Exposure time: 28 d

Method: OECD Test Guideline 301B

GLP: yes

White mineral oil (petroleum):

Biodegradability : Test Type: Primary biodegradation

Inoculum: activated sludge Result: Not rapidly biodegradable

Biodegradation: 31 % Exposure time: 28 d

Method: OECD Test Guideline 301B

according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



STRUCTOVIS FHD Spray

Version Revision Date: Date of last issue: 05.01.2021 Print Date: 08.09.2021 Date of first issue: 19.06.2017 09.09.2021 1.8

12.3 Bioaccumulative potential

Product:

Bioaccumulation Remarks: This mixture contains no substance considered to

be persistent, bioaccumulating and toxic (PBT).

This mixture contains no substance considered to be very

persistent and very bioaccumulating (vPvB).

Components:

isobutane:

Partition coefficient: n-

log Pow: 2,88

octanol/water Method: OECD Test Guideline 107

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Partition coefficient: n-

octanol/water

: log Pow: > 2

White mineral oil (petroleum):

Partition coefficient: n-

octanol/water

Pow: > 6

propane:

Partition coefficient: n-

octanol/water

log Pow: 2,36

butane:

Partition coefficient: n-

log Pow: 2,89

octanol/water

Method: OECD Test Guideline 107

12.4 Mobility in soil

Product:

Mobility Remarks: No data available

Distribution among environ-

mental compartments

Remarks: No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment This substance/mixture contains no components considered

> to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



STRUCTOVIS FHD Spray

Version Revision Date: Date of last issue: 05.01.2021 Print Date: 1.8 08.09.2021 Date of first issue: 19.06.2017 09.09.2021

Components:

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Assessment : Non-classified vPvB substance, Non-classified PBT sub-

stance.

White mineral oil (petroleum):

Assessment : Non-classified PBT substance. Non-classified vPvB sub-

stance.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

: No information on ecology is available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.

Dispose of as hazardous waste in compliance with local and

national regulations.

Waste codes should be assigned by the user based on the

application for which the product was used.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as

the unused product.

Offer empty spray cans to an established disposal company. Pressurized container: Do not pierce or burn, even after use.

The following Waste Codes are only suggestions:

Waste Code : unused product, packagings not completely emptied

16 05 04*, gases in pressure containers (including halons)

containing hazardous substances

according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



STRUCTOVIS FHD Spray

Version Revision Date: Date of last issue: 05.01.2021 Print Date: 1.8 08.09.2021 Date of first issue: 19.06.2017 09.09.2021

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 1950
ADR : UN 1950
RID : UN 1950
IMDG : UN 1950
IATA : UN 1950

14.2 UN proper shipping name

ADN : AEROSOLS
ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS

IATA : Aerosols, flammable

14.3 Transport hazard class(es)

ADN : 2
ADR : 2
RID : 2
IMDG : 2.1
IATA : 2.1

14.4 Packing group

ADN

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1

ADR

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1 Tunnel restriction code : (D)

RID

Packing group : Not assigned by regulation

Classification Code : 5F Hazard Identification Number : 23 Labels : 2.1

IMDG

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U

according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



STRUCTOVIS FHD Spray

Version Revision Date: Date of last issue: 05.01.2021 Print Date: 1.8 08.09.2021 Date of first issue: 19.06.2017 09.09.2021

IATA (Cargo)

Packing instruction (cargo

203

aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

IATA (Passenger)

Packing instruction (passen- : 203

ger aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

Not applicable

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

(EU SVHC)

This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH),

Article 57).

REACH - List of substances subject to authorisation

(Annex XIV)

(EU. REACH - Annex XIV)

: Not applicable

Regulation (EC) No 1005/2009 on substances that de- : Not applicable

a brand of

FREUDENBERG

according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



STRUCTOVIS FHD Spray

Version Revision Date: Date of last issue: 05.01.2021 Print Date: 1.8 08.09.2021 Date of first issue: 19.06.2017 09.09.2021

plete the ozone layer (EC 1005/2009)

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

(EU POP)

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

(EU PIC)

Regulation (EU) 2019/1148 on the marketing and use of :

explosives precursors

Not applicable

Not applicable

Not applicable

: P2

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous sub-

stances.

P3a FLAMMABLE AEROSOLS

18 Liquefied extremely flammable gases (including LPG) and natu-

ral gas

Water contaminating class

(Germany)

WGK 1 slightly hazardous to water

Classification according to AwSV, Annex 1 (5.2)

TA Luft List (Germany) Total dust:

others: 0,6 %

Inorganic substances in powdered form:

Not applicable

Inorganic substances in vapour or gaseous form:

Not applicable Organic Substances: portion Class 1: < 0,01 %

others: 99,35 %

Carcinogenic substances: portion Class 3: 0,04 %

Mutagenic: others: 0,04 %

Toxic to reproduction:

Not applicable

Volatile organic compounds Directive 2010/75/EU of 24 November 2010 on industrial

according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



STRUCTOVIS FHD Spray

Version Revision Date: Date of last issue: 05.01.2021 Print Date: 1.8 08.09.2021 Date of first issue: 19.06.2017 09.09.2021

emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 48,04 %

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

This information is not available.

SECTION 16: Other information

Full text of H-Statements

H220 : Extremely flammable gas.

H280 : Contains gas under pressure; may explode if heated.

Full text of other abbreviations

Note C : Some organic substances may be marketed either in a specif-

ic isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the sub-

stance is a specific isomer or a mixture of isomers.

Note L : The classification as a carcinogen need not apply if it can be

shown that the substance contains less than 3 % DMSO extract as measured by IP 346 "Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions - Dimethyl sulphoxide extraction refractive index method", Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.

Note U (table 3.1) : When put on the market gases have to be classified as "Gas-

es under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.) Aerosols shall not be classified as gases under pressure (See Annex I, Part

2, Section 2.3.2.1, Note 2).

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



STRUCTOVIS FHD Spray

Version Revision Date: Date of last issue: 05.01.2021 Print Date: 1.8 08.09.2021 Date of first issue: 19.06.2017 09.09.2021

the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP -Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL -International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS -Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Classification procedure:

Aerosol 1 H222, H229 Calculation method

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



STRUCTOVIS FHD Spray

VersionRevision Date:Date of last issue: 05.01.2021Print Date:1.808.09.2021Date of first issue: 19.06.201709.09.2021