MOTIF DUPLI GROUP

Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 30.07.2008 Revision: 30.07.2008

1 Identification of the substance/preparation and of the company/undertaking

· Product details

· Trade name: MOTIP ADHESIVE SPRAY

· Article number: 000575

· Application of the substance / the preparation Glue/ Sizing agent

· Manufacturer/Supplier:

MOTIP DUPLI B.V.

Wolfraamweg 2

NL-8471 XC Wolvega

The Netherlands

Tel: +31 (0)561 694400 Fax: +31 (0)561 694411 e-mail info@nl.motipdupli.com

· Further information obtainable from: QHSE Department

Information in case of emergency: Tel: +31 (0)561 694400 (08.00 / 17.00)

2 Hazards identification

· Hazard description:







Xi Irritant

F+ Extremely flammable

N Dangerous for the environment

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurized container.

Has a narcotizing effect.

R 12 Extremely flammable.

R 38 Irritating to skin.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 67 Vapours may cause drowsiness and dizziness.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

Keep out of the reach of children

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data

· GHS label elements



Danger

2.2/1 - Extremely flammable gas.

2.3/1 - Extremely flammable aerosol.



Warning

3.2/2 - Causes skin irritation.

3.8/3 - May cause drowsiness or dizziness.

(Contd. on page 2)

Printing date 30.07.2008 Revision: 30.07.2008

Trade name: MOTIP ADHESIVE SPRAY



4.1/2 - Toxic to aquatic life with long lasting effects.

· Prevention:

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face protection.

· Response:

IF ON SKIN: Wash with plenty of soap and water.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

Call a POISON CENTER or doctor/physician if you feel unwell.

Specific treatment (see label).

If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing and wash before reuse.

Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

Eliminate all ignition sources if safe to do so.

Collect spillage.

· Storage:

Store in a well-ventilated place.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Protect from sunlight. Do no expose to temperatures exceeding 50°C/122°F.

· Disposal:

Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

- · Chemical characterization
- **Description:** Mixture of substances listed below with nonhazardous additions.

CAS: 64742-49-0	Naphtha (petroleum), hydrotreated light	25-50%
	X_{n} X_{i} X_{i	
	Danger: (4) 2.6/2; (4) 3.10/1	
	Warning: (1) 3.2/2, 3.8/3	
	♦ 4.1.C/2	•
CAS: 109-66-0	pentane	12.5-20%
EINECS: 203-692-4	Xn, Hr, Kn, R 12-51/53-65-66-67	
	Danger: (b) 2.6/1; (c) 3.10/1	
	Warning: 🚺 3.8/3	
	♦ 4.1.C/2	
CAS: 115-10-6	dimethyl ether	12.5-20%
EINECS: 204-065-8	♦ F+; R 12	
	Danger: 🚸 2.2/1	
	Warning: 🔷 2.5/L	

GB ·

(Contd. of page 1)

Printing date 30.07.2008 Revision: 30.07.2008

Trade name: MOTIP ADHESIVE SPRAY

CAS: 74-98-6	propane	(Contd. of page 5-10%
EINECS: 200-827-	9 F+; R 12	
	Danger: (b) 2.2/1	
	Warning: 🔷 2.5/L	
CAS: 106-97-8	butane	2.5-5%
EINECS: 203-448-	7 8 F+; R 12	
	Danger: 🚸 2.2/1	
	Warning: <a>2.5/L	
CAS: 75-28-5	isobutane	2.5-5%
EINECS: 200-857-	2 F+; R 12	
	Danger: (b) 2.2/1	
	Warning: <a>2.5/L	
CAS: 78-93-3	butanone	2.5-5%
EINECS: 201-159-	0 Xi, 🔥 F; R 11-36-66-67	
	Danger: (b) 2.6/2	
	Warning: (1) 3.3/2A, 3.8/3	

4 First-aid measures

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.

5 Fire-fighting measures

- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Person-related safety precautions: Ensure adequate ventilation
- · Measures for environmental protection:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· Measures for cleaning/collecting: Ensure adequate ventilation.

7 Handling and storage

- · Handling:
- · Information for safe handling:

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 4)

Printing date 30.07.2008 Revision: 30.07.2008

Trade name: MOTIP ADHESIVE SPRAY

(Contd. of page 3)

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

8 Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· Aaaimoi	nai information about aesign of technical facilities: No further data; see tiem 7.
· Ingredi	ents with limit values that require monitoring at the workplace:
109-66-	0 pentane
WEL ()	Long-term value: 1800 mg/m³, 600 ppm
115-10-	6 dimethyl ether
WEL ()	Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm
106-97-	8 butane
WEL ()	Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
78-93-3	butanone
WEL ()	Short-term value: 899 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm Sk

- · Additional information: The lists valid during the making were used as basis.
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

- · Respiratory protection: Not required.
- · Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.



Protective gloves

· Material of gloves

(Contd. on page 5)

Printing date 30.07.2008 Revision: 30.07.2008

Trade name: MOTIP ADHESIVE SPRAY

(Contd. of page 4)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Not required.

~	
General Information	
Form:	Aerosol
Colour:	According to product specification
Odour:	Characteristic
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Not applicable, as aerosol.
Flash point:	< 0°C (< 32°F)
•	Not applicable, as aerosol.
Ignition temperature:	235°C (455°F)
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	1.1 Vol %
Upper:	18.6 Vol %
Vapour pressure at 20°C (68°F).	: 4000 hPa (3000 mm Hg)
Density at 20°C (68°F):	0.699 g/cm^3
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Solvent content:	
Organic solvents:	84.0 %
EU-VOC:	587.4 g/l

10 Stability and reactivity

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Dangerous reactions No dangerous reactions known.
- · Dangerous decomposition products: No dangerous decomposition products known.

GB

Printing date 30.07.2008 Revision: 30.07.2008

Trade name: MOTIP ADHESIVE SPRAY

(Contd. of page 5)

11 Toxicological information

· Acute toxicity:

· LD/LC5	· LD/LC50 values relevant for classification:			
64742-4	64742-49-0 Naphtha (petroleum), hydrotreated light			
Oral	LD50	>5000 mg/kg (rat)		
Dermal	LD50	>2600 mg/kg (rabbit)		
	LC50 / 4 h	>193 mg/m3 (rat)		
109-66-6	109-66-0 pentane			
Oral	LD50	>16000 mg/kg (rat)		
Dermal	LD50	>2500 mg/kg (rat)		
		>5000 mg/kg (rabbit)		
	LC50 / 4 h	>100 mg/m3 (rat)		
115-10-0	115-10-6 dimethyl ether			
	LC50 / 4 h	308 mg/m3 (rat)		
106-97-8	106-97-8 butane			
	LC50 / 4 h	658 mg/m3 (rat)		
78-93-3	78-93-3 butanone			
Oral	LD50	2737 mg/kg (rat)		
Dermal	LD50	6480 mg/kg (rabbit)		
	LC50 / 4 h	34 mg/m3 (rat)		

- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

12 Ecological information

· Ecotoxical effects:

· Acquatic to	Acquatic toxicity:		
64742-49-0 Naphtha (petroleum), hydrotreated light			
LC50	127-159 mg/l (Leuciscus idus)		
109-66-0 ре	109-66-0 pentane		
EC50 / 48 P	n 9.7 mg/l (daphnia magna)		
115-10-6 dimethyl ether			
EC50 / 48 I	n >4000 mg/l (daphnia magna)		

- · Remark: Toxic for fish
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

GE

Printing date 30.07.2008 Revision: 30.07.2008

Trade name: MOTIP ADHESIVE SPRAY

(Contd. of page 6)

13 Disposal considerations

- · Product:
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

20 01 13 solvents

15 01 04 metallic packaging

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

· Land transport ADR/RID (cross-border)



2 5F Gases. · ADR/RID class:

· Danger code (Kemler): -

· UN-Number: 1950 · Packaging group: · Hazard label 2.1

· Description of goods: 1950 AEROSOLS

· Limited quantities (LQ) LQ2

· Transport category

· Tunnel restriction code B1D

· Maritime transport IMDG:



· IMDG Class: 2.1 1950 · UN Number: 2.1 · Label · Packaging group:

F-D,S-U· EMS Number: · Marine pollutant:

· Proper shipping name: AEROSOLS

· Air transport ICAO-TI and IATA-DGR:



· ICAO/IATA Class: · UN/ID Number: 1950 · Label 2.1 · Packaging group:

· Proper shipping name: AEROSOLS, flammable

· UN "Model Regulation": UN1950, AEROSOLS, 2.1

Printing date 30.07.2008 Revision: 30.07.2008

Trade name: MOTIP ADHESIVE SPRAY

(Contd. of page 7)

15 Regulatory information

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:







- Xi Irritant
- F+ Extremely flammable
- N Dangerous for the environment

· Risk phrases:

- 12 Extremely flammable.
- 38 Irritating to skin.
- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 67 Vapours may cause drowsiness and dizziness.

· Safety phrases:

- 2 Keep out of the reach of children.
- 23 Do not breathe aerosol.
- 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
- 46 If swallowed, seek medical advice immediately and show this container or label.
- 51 Use only in well-ventilated areas.

· Special labelling of certain preparations:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

Keep out of the reach of children

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant R-phrases

- 11 Highly flammable.
- 12 Extremely flammable.
- 36 Irritating to eyes.
- 38 Irritating to skin.
- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 65 Harmful: may cause lung damage if swallowed.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.

· Department issuing MSDS: QHSE Department

· Contact:

Mrs. D. Kleistra

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Reglement internationale concernent le transport des merchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

(Contd. on page 9)

Page 9/9

Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 30.07.2008 Revision: 30.07.2008

Trade name: MOTIP ADHESIVE SPRAY

(Contd. of page 8)

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO) GHS: Globally Harmonized System of Classification and Labelling of Chemicals LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

· * Data compared to the previous version altered.