



**Specialty  
Lubricants**

**MOLYKOTE® MKL-N  
Dispersion**

**FEATURES**

- Penetration
- Adhesion
- Protection against wear
- Corrosion protection
- Ageing stability

**COMPOSITION**

- Mineral oil
- Inhibitors
- Adhesion improver
- Solid lubricants
- Solvents

**Mineral oil grease with solid lubricants dispersed in solvent**

**APPLICATION**

- Used for lubrication of chains.

**TYPICAL PROPERTIES**

Specification writers: These values are not intended for use in preparing specifications. Please contact your local Dow Corning sales representative prior to writing specifications on this product.

<b>Standard*</b>	<b>Test</b>	<b>Unit</b>	<b>Result</b>
	Color		Black
	<b>Density</b>		
	Density at 20°C	g/ml	0.87
	<b>Load-carrying capacity, wear protection</b>		
	Four-ball tester (VKA)		
DIN 51 350 pt.4	Weld load	N	1200
DIN 51 350 pt.5	Wear scar under 800N load	mm	0.9
	<b>Corrosion protection</b>		
DIN 51 802	SKF-Emcor method		
	Degree of corrosion		0-1

\* DIN: Deutsche Industrie Norm

**HOW TO USE**

**How to apply**

Apply thinly to clean, dry surfaces using a brush. Small chains can also be dipped. The chain can be used after evaporation of the solvent (approx. 30 minutes).

**HANDLING PRECAUTIONS**

PRODUCT SAFETY INFORMATION REQUIRED FOR SAFE USE IS NOT INCLUDED. BEFORE HANDLING, READ PRODUCT AND SAFETY DATA SHEETS AND CONTAINER LABELS FOR SAFE USE, PHYSICAL AND HEALTH HAZARD INFORMATION. THE SAFETY DATA SHEET IS AVAILABLE FROM YOUR LOCAL DOW CORNING SALES REPRESENTATIVE.

**USABLE LIFE AND STORAGE**

When stored at or below 20°C in the original unopened containers, this product has a usable life of 36 months from the date of production.

**PACKAGING**

This product is available in different standard container sizes. Detailed container size information should be obtained from your nearest Dow Corning sales office or Dow Corning distributor.

**LIMITATIONS**

This product is neither tested nor represented as suitable for medical or pharmaceutical uses.

## **HEALTH AND ENVIRONMENTAL INFORMATION**

To support customers in their product safety needs, Dow Corning has an extensive Product Stewardship organization and a team of Health, Environment and Regulatory Affairs specialists available in each area.

For further information, please consult your local Dow Corning representative.

## **WARRANTY INFORMATION - PLEASE READ CAREFULLY**

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that Dow Corning's products are safe, effective, and fully satisfactory for the intended end use. Dow Corning's sole warranty is that the product will meet the Dow Corning sales specifications in effect at the time of shipment. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted. Dow Corning specifically disclaims any other express or implied warranty of fitness for a particular purpose or merchantability. Unless Dow Corning provides you with a specific, duly signed endorsement of fitness for use, Dow Corning disclaims liability for any incidental or consequential damages. Suggestions of use shall not be taken as inducements to infringe any patent.