

## Castrol Hysol RD

High performance semi-synthetic metalworking fluid

### Description

Castrol Hysol™ RD is a high performance chlorine free semi-synthetic metalworking fluid. It contains a unique additive package that works in synergy to enhance machining performance and surface finish, provide excellent product stability, improve bio-resistance properties and lower the overall operations costs.

Hysol RD is suitable for large central systems and single sump machines.

### Application

Hysol RD is especially designed for machining of cast iron and low-medium alloyed steel.

	Cast Iron	Low-medium alloyed steel	High alloyed - stainless steel	Aluminium alloys	Magnesium alloys	Yellow metals
Grinding	✓✓✓	✓✓	✓✓			
Milling, Turning (general machining)	✓✓✓	✓✓	✓			
Drilling	✓✓✓	✓✓				
Reaming, Tapping	✓✓✓	✓				
Broaching	✓✓✓	✓				

### Advantages

- Chlorine and nitrite free to fulfill your local legislation, waste treatment and environmental requirements
- Resists fungal and bacterial attack to extend fluid life and reduce maintenance and machine downtime
- Low foam in recommended water conditions
- Excellent anti-corrosion properties to protect machine tools and parts
- Advanced lubricity compounds ensure improved tool life and part quality
- Excellent wetting properties reduce coolant drag out and deliver clean machine tools and components

## Typical Characteristics

	Test Method	Unit	Value
<b>Concentrate</b>			
Appearance	Visual		Amber
Mineral oil content	Calculated	Wt%	35
<b>Emulsion</b>			
Appearance	Visual		Transparent
pH (5%)	DIN 51361 ASTM E70-97		9.0
Refractometer Factor			1.1

	Boron	Formaldehyde releasing agent	EP-Ester	Amines	Chlorine
Additives	✓	✓	-	✓	-

## Recommended Concentrations

Grinding	4-6%
General Machining	5-7%
Drilling	6-8%
Reaming and tapping	6-8%
Broaching	6-8%
Water range	100-400 ppm CaCO <sub>3</sub>

## Storage

To avoid product deterioration, keep the container/drum tightly sealed always. Prevent any frost and water ingress.

Store it in a cool and dry place away from direct sunlight. It is preferable to store the product indoors always. For more details, please refer the product safety data sheet.

Castrol, Hysol, and the Castrol logo are trademarks of Castrol Limited, used under licence

INTERNATIONAL. All reasonable care has been taken to ensure that the information contained in this publication is accurate as of the date of printing. However, such information may, nevertheless, be affected by changes in the blend formulation occurring subsequent to the date of printing. Material Safety Data Sheets are available for all Castrol Ltd products. The MSDS must be consulted for appropriate information regarding storage, safe handling and disposal of a product.

Castrol Limited, Pipers Way, Swindon, Wiltshire SN3 1RE, UK  
[www.castrol.com/industrial](http://www.castrol.com/industrial)

Castrol Hysol RD  
 10 October 2008 Version 1