

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



Klübersynth UH1 14-222

Version	Revision Date:	Date of last issue: 07.01.2021	Print Date:
1.9	30.06.2021	Date of first issue: 08.03.2016	01.07.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Klübersynth UH1 14-222

Article-No. : 096071

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Grease

Recommended restrictions
on use : Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company : Klüber Lubrication München
Geisenhausenerstr. 7
81379 München
Deutschland
Tel: +49 (0) 89 7876 0
Fax: +49 (0) 89 7876 333
info@klueber.com

E-mail address of person
responsible for the SDS : mcm@klueber.com
Material Compliance Management

National contact : Klüber Lubrication Deutschland
Geisenhausenerstraße 7
81379 München
Deutschland
Tel.: +49 89 7876 0
Fax: +49 89 7876 565
customer.service.de@klueber.com
www.klueber.com

1.4 Emergency telephone number

Emergency telephone num-
ber : +49 89 7876 700 (24 hrs)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Long-term (chronic) aquatic hazard, Cat- H412: Harmful to aquatic life with long lasting ef-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



Klübersynth UH1 14-222

Version 1.9	Revision Date: 30.06.2021	Date of last issue: 07.01.2021 Date of first issue: 08.03.2016	Print Date: 01.07.2021
----------------	------------------------------	---	---------------------------

Category 3

effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard statements : H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P273 Avoid release to the environment.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Synthetic hydrocarbon oil
ester oil
aluminium complex soap
solid lubricant

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration limits M-Factor Notes	Concentration (% w/w)
disodium sebacate	17265-14-4 241-300-3 01-2120762063-61-XXXX	Eye Irrit.2; H319		$\geq 1 - < 10$
White mineral oil (petroleum)	8042-47-5 232-455-8 01-2119487078-27-XXXX	Asp. Tox.1; H304		$\geq 1 - < 10$
2,6-di-tert-butyl-p-cresol	128-37-0 204-881-4 01-2119555270-46-XXXX	Aquatic Acute1; H400 Aquatic Chronic1; H410	M-Factor: 1/1	$\geq 0,25 - < 1$

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



Klübersynth UH1 14-222

Version 1.9	Revision Date: 30.06.2021	Date of last issue: 07.01.2021 Date of first issue: 08.03.2016	Print Date: 01.07.2021
----------------	------------------------------	---	---------------------------

Amines, C12-14-alkyl, isooctyl phosphates	68187-67-7 269-119-5 01-2120286234-55-XXXX	Acute Tox.4; H302 Acute Tox.4; H312 Skin Corr.1C; H314 Eye Dam.1; H318 Aquatic Acute1; H400 Aquatic Chronic1; H410	M-Factor: 1/1	$\geq 0,25 - < 1$
N-methyl-N-[C18-(unsaturated)alkanoyl]glycine	701-177-3 01-2119488991-20-XXXX	Acute Tox.4; H332 Skin Irrit.2; H315 Eye Dam.1; H318 Aquatic Acute1; H400 Aquatic Chronic3; H412	M-Factor: 1/	$\geq 0,25 - < 1$
Substances with a workplace exposure limit :				
White mineral oil (petroleum)	8042-47-5 232-455-8 01-2119487078-27-XXXX	Not classified		$\geq 1 - < 10$

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- | | |
|-------------------------|--|
| If inhaled | : Remove person to fresh air. If signs/symptoms continue, get medical attention.
Keep patient warm and at rest.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
If breathing is irregular or stopped, administer artificial respiration. |
| In case of skin contact | : Remove contaminated clothing. If irritation develops, get medical attention.
Wash off with soap and water.
Wash clothing before reuse.
Thoroughly clean shoes before reuse. |
| In case of eye contact | : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.
If eye irritation persists, consult a specialist. |
| If swallowed | : Move the victim to fresh air.
If unconscious, place in recovery position and seek medical advice. |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



Klübersynth UH1 14-222

Version	Revision Date:	Date of last issue: 07.01.2021	Print Date:
1.9	30.06.2021	Date of first issue: 08.03.2016	01.07.2021

Keep respiratory tract clear.
Do not induce vomiting without medical advice.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No information available.

Risks : None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : Carbon oxides
Nitrogen oxides (NO_x)
Oxides of phosphorus
Metal oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. Exposure to decomposition products may be a hazard to health.

Further information : Standard procedure for chemical fires.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.
Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust).
Do not breathe vapours, aerosols.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



Klübersynth UH1 14-222

Version	Revision Date:	Date of last issue: 07.01.2021	Print Date:
1.9	30.06.2021	Date of first issue: 08.03.2016	01.07.2021

Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Clean up promptly by sweeping or vacuum. Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Wash hands and face before breaks and immediately after handling the product. Do not ingest. Do not repack. These safety instructions also apply to empty packaging which may still contain product residues. Keep container closed when not in use.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Keep container closed when not in use. Keep in a dry, cool and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with the particular national regulations. Keep in properly labelled containers.

Storage class (TRGS 510) : 11, Combustible Solids

7.3 Specific end use(s)

Specific use(s) : Specific instructions for handling, not required.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE

KLÜBER
LUBRICATION

Klübersynth UH1 14-222

Version	Revision Date:	Date of last issue: 07.01.2021	Print Date:
1.9	30.06.2021	Date of first issue: 08.03.2016	01.07.2021

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
White mineral oil (petroleum)	8042-47-5	AGW (Alveolate fraction)	5 mg/m ³	DE TRGS 900 (2015-11-06)
Peak-limit: excursion factor (category)	4;(II)			
Further information	When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
White mineral oil (petroleum)	8042-47-5	AGW (Alveolate fraction)	5 mg/m ³	DE TRGS 900 (2015-11-06)
Peak-limit: excursion factor (category)	4;(II)			
Further information	When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
2,6-di-tert-butyl-p-cresol	128-37-0	AGW (Vapour and aerosols, inhalable fraction)	10 mg/m ³	DE TRGS 900 (2012-09-13)
Peak-limit: excursion factor (category)	4;(II)			
Further information	When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
N-methyl-N-[C18-(unsaturated)alkanoyl]glycine	Not Assigned	AGW (Inhalable fraction)	0,05 mg/m ³	DE TRGS 900 (2019-03-29)
Peak-limit: excursion factor (category)	2;(II)			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
White mineral oil (petroleum)	Workers	Inhalation	Long-term systemic effects	160 mg/m ³
	Workers	Skin contact	Long-term systemic effects	220 mg/kg
disodium sebacate	Workers	Skin contact	Long-term systemic effects	10 mg/kg
	Workers	Inhalation	Long-term systemic effects	35,26 mg/m ³
White mineral oil (pe-	Workers	Inhalation	Long-term systemic	160 mg/m ³

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



Klübersynth UH1 14-222

Version	Revision Date:	Date of last issue: 07.01.2021	Print Date:
1.9	30.06.2021	Date of first issue: 08.03.2016	01.07.2021

troleum)			effects	
	Workers	Dermal	Long-term systemic effects	220 mg/kg bw/day
2,6-di-tert-butyl-p-cresol	Workers	Inhalation	Long-term systemic effects	3,5 mg/m3
	Workers	Skin contact	Long-term systemic effects	0,5 mg/kg
N-methyl-N-[C18-(unsaturated)alkanoyl]glycine	Workers	Inhalation	Long-term systemic effects	0,8 mg/m3
	Workers	Skin contact	Long-term systemic effects	4,2 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
disodium sebacate	Fresh water	0,018 mg/l
	Marine water	0,002 mg/l
	Sewage treatment plant	10 mg/l
	Fresh water sediment	0,548 mg/kg
	Marine sediment	0,055 mg/kg
	Soil	0,099 mg/kg
2,6-di-tert-butyl-p-cresol	Fresh water	0,199 µg/l
	Marine water	0,02 µg/l
	Intermittent use/release	1,99 µg/l
	Microbiological Activity in Sewage Treatment Systems	0,17 mg/l
	Fresh water sediment	0,0996 mg/kg
	Marine sediment	0,00996 mg/kg
N-methyl-N-[C18-(unsaturated)alkanoyl]glycine	Soil	0,04769 mg/kg
	Oral	8,33 mg/kg
	Fresh water	0,00043 mg/l
	Marine water	0,000043 mg/l
	Microbiological Activity in Sewage Treatment Systems	1 mg/l
	Fresh water sediment	0,057 mg/kg
	Marine sediment	0,006 mg/kg
	Soil	1,71 mg/kg

8.2 Exposure controls

Engineering measures

none

Personal protective equipment

Eye protection : Safety glasses with side-shields

Hand protection

Material : Nitrile rubber
Break through time : > 10 min
Protective index : Class 1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



Klübersynth UH1 14-222

Version 1.9	Revision Date: 30.06.2021	Date of last issue: 07.01.2021 Date of first issue: 08.03.2016	Print Date: 01.07.2021
----------------	------------------------------	---	---------------------------

Remarks	: For prolonged or repeated contact use protective gloves. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case. The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.
Respiratory protection	: Not required; except in case of aerosol formation.
Filter type	: Filter type P
Protective measures	: The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: paste
Colour	: beige
Odour	: characteristic
Odour Threshold	: No data available
pH	: No data available
Melting point/range	: No data available
Boiling point/boiling range	: No data available
Flash point	: Not applicable
Evaporation rate	: No data available
Flammability (solid, gas)	: Combustible Solids
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower	: No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



Klübersynth UH1 14-222

Version 1.9	Revision Date: 30.06.2021	Date of last issue: 07.01.2021 Date of first issue: 08.03.2016	Print Date: 01.07.2021
----------------	------------------------------	---	---------------------------

flammability limit

Vapour pressure : < 0,001 hPa (20 °C)

Relative vapour density : No data available

Relative density : 0,94 (20 °C)
Reference substance: Water
The value is calculated

Density : 0,94 g/cm³
(20 °C)

Bulk density : No data available

Solubility(ies)
Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity
Viscosity, dynamic : No data available

Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : No data available

9.2 Other information

Sublimation point : No data available

Self-ignition : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No hazards to be specially mentioned.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



Klübersynth UH1 14-222

Version	Revision Date:	Date of last issue: 07.01.2021	Print Date:
1.9	30.06.2021	Date of first issue: 08.03.2016	01.07.2021

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : No conditions to be specially mentioned.

10.5 Incompatible materials

Materials to avoid : No materials to be especially mentioned.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product:

Acute oral toxicity : Remarks: This information is not available.

Acute inhalation toxicity : Remarks: This information is not available.

Acute dermal toxicity : Remarks: This information is not available.

Components:

disodium sebacate:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Method: OECD Test Guideline 401
GLP: no

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg
Method: OECD Test Guideline 402
GLP: yes
Assessment: The substance or mixture has no acute dermal toxicity

White mineral oil (petroleum):

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



Klübersynth UH1 14-222

Version 1.9	Revision Date: 30.06.2021	Date of last issue: 07.01.2021 Date of first issue: 08.03.2016	Print Date: 01.07.2021
----------------	------------------------------	---	---------------------------

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

2,6-di-tert-butyl-p-cresol:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 5.000 mg/kg
Method: OECD Test Guideline 402

Amines, C12-14-alkyl, isooctyl phosphates:

Acute oral toxicity : LD50 (Rat): 1.000 mg/kg
Method: OECD Test Guideline 423
GLP: yes

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

Acute dermal toxicity : LD50 (Rabbit): 2.000 mg/kg
Method: OECD Test Guideline 402
GLP: yes

N-methyl-N-[C18-(unsaturated)alkanoyl]glycine:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat, male): 1,05 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

White mineral oil (petroleum):

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Method: OECD Test Guideline 401
GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
GLP: yes
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg
Method: OECD Test Guideline 402
GLP: yes
Assessment: The substance or mixture has no acute dermal toxicity

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



Klübersynth UH1 14-222

Version	Revision Date:	Date of last issue: 07.01.2021	Print Date:
1.9	30.06.2021	Date of first issue: 08.03.2016	01.07.2021

Skin corrosion/irritation

Product:

Remarks : This information is not available.

Components:

disodium sebacate:

Species : Rabbit
Assessment : No skin irritation
Method : OECD Test Guideline 404
Result : No skin irritation
GLP : no

White mineral oil (petroleum):

Species : Rabbit
Assessment : No skin irritation
Method : OECD Test Guideline 404
Result : No skin irritation
GLP : yes

2,6-di-tert-butyl-p-cresol:

Species : Rabbit
Assessment : No skin irritation
Result : No skin irritation

Amines, C12-14-alkyl, isooctyl phosphates:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Corrosive, category 1C - where responses occur after exposures between 1 hour and 4 hours and observations up to 14 days.
GLP : yes

N-methyl-N-[C18-(unsaturated)alkanoyl]glycine:

Species : Rabbit
Assessment : Irritating to skin.
Result : Irritating to skin.

White mineral oil (petroleum):

Species : Rabbit
Assessment : No skin irritation
Method : OECD Test Guideline 404
Result : No skin irritation
GLP : yes

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



Klübersynth UH1 14-222

Version	Revision Date:	Date of last issue: 07.01.2021	Print Date:
1.9	30.06.2021	Date of first issue: 08.03.2016	01.07.2021

Serious eye damage/eye irritation

Product:

Remarks : This information is not available.

Components:

disodium sebacate:

Species : Rabbit
Assessment : Irritating to eyes.
Method : OECD Test Guideline 437
Result : Irritating to eyes.
GLP : yes

White mineral oil (petroleum):

Species : Rabbit
Assessment : No eye irritation
Method : OECD Test Guideline 405
Result : No eye irritation
GLP : yes

2,6-di-tert-butyl-p-cresol:

Species : Rabbit
Assessment : No eye irritation
Method : Draize Test
Result : No eye irritation

Amines, C12-14-alkyl, isooctyl phosphates:

Assessment : Risk of serious damage to eyes.
Result : Risk of serious damage to eyes.

N-methyl-N-[C18-(unsaturated)alkanoyl]glycine:

Species : Rabbit
Assessment : Risk of serious damage to eyes.
Result : Risk of serious damage to eyes.

White mineral oil (petroleum):

Species : Rabbit
Assessment : No eye irritation
Method : OECD Test Guideline 405
Result : No eye irritation
GLP : yes

Respiratory or skin sensitisation

Product:

Remarks : This information is not available.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



Klübersynth UH1 14-222

Version	Revision Date:	Date of last issue: 07.01.2021	Print Date:
1.9	30.06.2021	Date of first issue: 08.03.2016	01.07.2021

Components:

disodium sebacate:

Species	:	Guinea pig
Assessment	:	Did not cause sensitisation on laboratory animals.
Result	:	Did not cause sensitisation on laboratory animals.

White mineral oil (petroleum):

Test Type	:	Buehler Test
Species	:	Guinea pig
Assessment	:	Does not cause skin sensitisation.
Method	:	OECD Test Guideline 406
Result	:	Does not cause skin sensitisation.
GLP	:	yes

2,6-di-tert-butyl-p-cresol:

Species	:	Humans
Assessment	:	Does not cause skin sensitisation.
Result	:	Does not cause skin sensitisation.

Amines, C12-14-alkyl, isooctyl phosphates:

Species	:	Guinea pig
Assessment	:	Did not cause sensitisation on laboratory animals.
Method	:	OECD Test Guideline 406
Result	:	Did not cause sensitisation on laboratory animals.
GLP	:	yes

N-methyl-N-[C18-(unsaturated)alkanoyl]glycine:

Test Type	:	Maximisation Test
Species	:	Guinea pig
Assessment	:	Does not cause skin sensitisation.
Method	:	OECD Test Guideline 406
Result	:	Does not cause skin sensitisation.

White mineral oil (petroleum):

Test Type	:	Maximisation Test
Species	:	Guinea pig
Assessment	:	Does not cause skin sensitisation.
Method	:	OECD Test Guideline 406
Result	:	Does not cause skin sensitisation.
GLP	:	yes

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



Klübersynth UH1 14-222

Version 1.9	Revision Date: 30.06.2021	Date of last issue: 07.01.2021 Date of first issue: 08.03.2016	Print Date: 01.07.2021
----------------	------------------------------	---	---------------------------

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Components:

disodium sebacate:

Germ cell mutagenicity- Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

White mineral oil (petroleum):

Germ cell mutagenicity- Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

2,6-di-tert-butyl-p-cresol:

Genotoxicity in vitro : Test Type: Ames test
Result: negative
Remarks: In vitro tests did not show mutagenic effects

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Result: negative

Germ cell mutagenicity- Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

Amines, C12-14-alkyl, isooctyl phosphates:

Germ cell mutagenicity- Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

White mineral oil (petroleum):

Genotoxicity in vitro : Test Type: Ames test
Method: Mutagenicity (Salmonella typhimurium - reverse mutation assay)
Result: negative
GLP: yes

Germ cell mutagenicity- Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

Carcinogenicity

Product:

Remarks : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



Klübersynth UH1 14-222

Version	Revision Date:	Date of last issue: 07.01.2021	Print Date:
1.9	30.06.2021	Date of first issue: 08.03.2016	01.07.2021

Components:

White mineral oil (petroleum):

Carcinogenicity - Assessment : No evidence of carcinogenicity in animal studies.

White mineral oil (petroleum):

Carcinogenicity - Assessment : No evidence of carcinogenicity in animal studies.

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

Components:

disodium sebacate:

Reproductive toxicity - Assessment : No toxicity to reproduction
No effects on or via lactation

White mineral oil (petroleum):

Reproductive toxicity - Assessment : No toxicity to reproduction
No effects on or via lactation

2,6-di-tert-butyl-p-cresol:

Reproductive toxicity - Assessment : No toxicity to reproduction

White mineral oil (petroleum):

Reproductive toxicity - Assessment : No toxicity to reproduction
No effects on or via lactation

STOT - single exposure

Components:

White mineral oil (petroleum):

Assessment : The substance or mixture is not classified as specific target organ toxicant, single exposure.

2,6-di-tert-butyl-p-cresol:

Assessment : The substance or mixture is not classified as specific target organ toxicant, single exposure.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



Klübersynth UH1 14-222

Version	Revision Date:	Date of last issue: 07.01.2021	Print Date:
1.9	30.06.2021	Date of first issue: 08.03.2016	01.07.2021

White mineral oil (petroleum):

Assessment : The substance or mixture is not classified as specific target organ toxicant, single exposure.

STOT - repeated exposure

Components:

White mineral oil (petroleum):

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

2,6-di-tert-butyl-p-cresol:

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

White mineral oil (petroleum):

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Repeated dose toxicity

Product:

Remarks : This information is not available.

Components:

White mineral oil (petroleum):

NOAEL : 1.800 mg/kg
Exposure time : 90 d

Aspiration toxicity

Product:

This information is not available.

Components:

disodium sebacate:

No aspiration toxicity classification

White mineral oil (petroleum):

May be fatal if swallowed and enters airways.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



Klübersynth UH1 14-222

Version 1.9	Revision Date: 30.06.2021	Date of last issue: 07.01.2021 Date of first issue: 08.03.2016	Print Date: 01.07.2021
----------------	------------------------------	---	---------------------------

2,6-di-tert-butyl-p-cresol:

No aspiration toxicity classification

White mineral oil (petroleum):

No aspiration toxicity classification

Further information

Product:

Remarks : Information given is based on data on the components and the toxicology of similar products.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae/aquatic plants : Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

Components:

disodium sebacate:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 96 h
Test Type: semi-static test
Method: OECD Test Guideline 203
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Test Type: semi-static test
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae/aquatic plants : EL50 (Skeletonema costatum (marine diatom)): 38,7 mg/l
Exposure time: 72 h
Test Type: static test
Method: ISO 10253

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



Klübersynth UH1 14-222

Version 1.9	Revision Date: 30.06.2021	Date of last issue: 07.01.2021 Date of first issue: 08.03.2016	Print Date: 01.07.2021
----------------	------------------------------	---	---------------------------

GLP: yes

White mineral oil (petroleum):

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Test Type: semi-static test
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- Toxicity to microorganisms : LC50 (Bacteria): > 1.000 mg/l
Exposure time: 40 h
Test Type: Growth inhibition
- Toxicity to fish (Chronic toxicity) : NOEC: > 100 mg/l
Exposure time: 28 d
Species: Oncorhynchus mykiss (rainbow trout)
Remarks: The value is given based on a SAR/AAR approach using OECD Toolbox, DEREK, VEGA QSAR models (CAESAR models), etc.
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: >= 1.000 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Remarks: The value is given based on a SAR/AAR approach using OECD Toolbox, DEREK, VEGA QSAR models (CAESAR models), etc.

2,6-di-tert-butyl-p-cresol:

- Toxicity to fish : LC50 (Danio rerio (zebra fish)): 0,57 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0,61 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): > 0,4 mg/l
Exposure time: 72 h
Method: Regulation (EC) No. 440/2008, Annex, C.3
- M-Factor (Acute aquatic toxicity) : 1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



Klübersynth UH1 14-222

Version	Revision Date:	Date of last issue: 07.01.2021	Print Date:
1.9	30.06.2021	Date of first issue: 08.03.2016	01.07.2021

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,316 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)

M-Factor (Chronic aquatic toxicity) : 1

Amines, C12-14-alkyl, isooctyl phosphates:

Toxicity to fish : LC0 (Danio rerio (zebra fish)): 1 mg/l
Exposure time: 96 h
Test Type: static test
Method: Regulation (EC) No. 440/2008, Annex, C.1
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 17 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): 0,8 mg/l
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: yes

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

N-methyl-N-[C18-(unsaturated)alkanoyl]glycine:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 0,43 mg/l
Exposure time: 96 h
Test Type: flow-through test
Method: OECD Test Guideline 203
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0,43 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 6,3 mg/l
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



Klübersynth UH1 14-222

Version	Revision Date:	Date of last issue: 07.01.2021	Print Date:
1.9	30.06.2021	Date of first issue: 08.03.2016	01.07.2021

M-Factor (Acute aquatic toxicity) : 1

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

White mineral oil (petroleum):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): > 100 mg/l
Exposure time: 48 h
Test Type: Immobilization
Method: OECD Test Guideline 202

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: >= 1.000 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Physico-chemical removability : Remarks: No data available

Components:

disodium sebacate:

Biodegradability : Result: Biodegradable
Biodegradation: 89 %
Exposure time: 28 d

White mineral oil (petroleum):

Biodegradability : Biodegradation: 31 %
Exposure time: 28 d

2,6-di-tert-butyl-p-cresol:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge
Result: Not rapidly biodegradable
Biodegradation: 4,5 %
Exposure time: 28 d
Method: OECD Test Guideline 301C

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



Klübersynth UH1 14-222

Version	Revision Date:	Date of last issue: 07.01.2021	Print Date:
1.9	30.06.2021	Date of first issue: 08.03.2016	01.07.2021

Amines, C12-14-alkyl, isooctyl phosphates:

Biodegradability : Result: Not rapidly biodegradable
Biodegradation: 35 %
Exposure time: 28 d
Method: Directive 67/548/EEC Annex V, C.4.D.
GLP: yes

N-methyl-N-[C18-(unsaturated)alkanoyl]glycine:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge
Result: rapidly biodegradable
Biodegradation: 85,2 %
Exposure time: 28 d

White mineral oil (petroleum):

Biodegradability : Test Type: Primary biodegradation
Inoculum: activated sludge
Result: Not rapidly biodegradable
Biodegradation: 31 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).
This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

Components:

disodium sebacate:

Partition coefficient: n-octanol/water : log Pow: -4,9 (20 °C)
pH: 7,8

White mineral oil (petroleum):

Partition coefficient: n-octanol/water : log Pow: > 6

2,6-di-tert-butyl-p-cresol:

Bioaccumulation : Bioconcentration factor (BCF): 598,4
Partition coefficient: n-octanol/water : log Pow: 5,1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



Klübersynth UH1 14-222

Version	Revision Date:	Date of last issue: 07.01.2021	Print Date:
1.9	30.06.2021	Date of first issue: 08.03.2016	01.07.2021

Amines, C12-14-alkyl, isooctyl phosphates:

Partition coefficient: n-octanol/water : log Pow: 1,87
Method: OECD Test Guideline 117
GLP: yes

N-methyl-N-[C18-(unsaturated)alkanoyl]glycine:

Partition coefficient: n-octanol/water : log Pow: 3,5 - 4,2

White mineral oil (petroleum):

Partition coefficient: n-octanol/water : Pow: > 6

12.4 Mobility in soil

Product:

Mobility : Remarks: No data available

Distribution among environmental compartments : Remarks: No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

Components:

White mineral oil (petroleum):

Assessment : This substance is not considered to be persistent, bioaccumulating and toxic (PBT)..

2,6-di-tert-butyl-p-cresol:

Assessment : Non-classified PBT substance. Non-classified vPvB substance.

White mineral oil (petroleum):

Assessment : Non-classified PBT substance. Non-classified vPvB substance.

12.6 Other adverse effects

Product:

Endocrine disrupting potential : The substance/mixture does not contain components consid-

according to Regulation (EC) No. 1907/2006 - DE



Klübersynth UH1 14-222

Version	Revision Date:	Date of last issue: 07.01.2021	Print Date:
1.9	30.06.2021	Date of first issue: 08.03.2016	01.07.2021

erial
 ered to have endocrine disrupting properties according to
 REACH Article 57(f) or Commission Delegated regulation
 (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at
 levels of 0.1% or higher.

Additional ecological information	: Harmful to aquatic life with long lasting effects.
-----------------------------------	--

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	: The product should not be allowed to enter drains, water courses or the soil. Do not dispose of with domestic refuse. Dispose of as hazardous waste in compliance with local and national regulations.
---------	--

Waste codes should be assigned by the user based on the application for which the product was used.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.
Dispose of waste product or used containers according to local regulations.

The following Waste Codes are only suggestions:

Waste Code	:	used product, unused product 12 01 12*, spent waxes and fats
		uncleaned packagings 15 01 10, packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

14.1 UN number

ADN	:	Not regulated as a dangerous good
ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA	:	Not regulated as a dangerous good

14.2 UN proper shipping name

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



Klübersynth UH1 14-222

Version 1.9	Revision Date: 30.06.2021	Date of last issue: 07.01.2021 Date of first issue: 08.03.2016	Print Date: 01.07.2021
----------------	------------------------------	---	---------------------------

ADN	: Not regulated as a dangerous good
ADR	: Not regulated as a dangerous good
RID	: Not regulated as a dangerous good
IMDG	: Not regulated as a dangerous good
IATA	: Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADN	: Not regulated as a dangerous good
ADR	: Not regulated as a dangerous good
RID	: Not regulated as a dangerous good
IMDG	: Not regulated as a dangerous good
IATA	: Not regulated as a dangerous good

14.4 Packing group

ADN	: Not regulated as a dangerous good
ADR	: Not regulated as a dangerous good
RID	: Not regulated as a dangerous good
IMDG	: Not regulated as a dangerous good
IATA (Cargo)	: Not regulated as a dangerous good
IATA (Passenger)	: Not regulated as a dangerous good

14.5 Environmental hazards

ADN	: Not regulated as a dangerous good
ADR	: Not regulated as a dangerous good
RID	: Not regulated as a dangerous good
IMDG	: Not regulated as a dangerous good
IATA (Passenger)	: Not regulated as a dangerous good
IATA (Cargo)	: Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	: This product does not contain substances of very high concern (Regu-
---	--

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



Klübersynth UH1 14-222

Version	Revision Date:	Date of last issue: 07.01.2021	Print Date:
1.9	30.06.2021	Date of first issue: 08.03.2016	01.07.2021

REACH - List of substances subject to authorisation (Annex XIV)	:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
Regulation (EU) 2019/1021 on persistent organic pollutants (recast)	:	Not applicable
Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals	:	Not applicable
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)	:	Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
Not applicable

Water contaminating class (Germany) : WGK 2 obviously hazardous to water
Classification according to AwSV, Annex 1 (5.2)

TA Luft List (Germany) : Total dust:
others: 15,09 %

Inorganic substances in powdered form:
Not applicable
Inorganic substances in vapour or gaseous form:
Not applicable
Organic Substances:
portion Class 1: 0,09 %
others: 84,07 %

Carcinogenic substances:
Not applicable
Mutagenic:
Not applicable
Toxic to reproduction:
Not applicable

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 0,75 %

15.2 Chemical safety assessment

This information is not available.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



Klübersynth UH1 14-222

Version	Revision Date:	Date of last issue: 07.01.2021	Print Date:
1.9	30.06.2021	Date of first issue: 08.03.2016	01.07.2021

SECTION 16: Other information

Full text of H-Statements

H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

DE TRGS 900	: Germany. TRGS 900 - Occupational exposure limit values.
DE TRGS 900 / AGW	: Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



Klübersynth UH1 14-222

Version	Revision Date:	Date of last issue: 07.01.2021	Print Date:
1.9	30.06.2021	Date of first issue: 08.03.2016	01.07.2021

Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Aquatic Chronic 3 H412

Classification procedure:

Calculation method

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.