

## Interflon Lube TF (Aerosol)

**Version number:**

5.6

Replaces version: (5)

25.02.2021

25.02.2021:

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name	<b>Interflon Lube TF (Aerosol)</b>
Registration number (REACH)	not relevant (mixture)
Unique formula identifier - UFI	0630-90YN-200A-5TCJ

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Scope	lubricant
-------	-----------

#### 1.3 Details of the supplier of the safety data sheet

Interflon BV  
Belder 47  
4704 RK Roosendaal  
Netherlands

Telephone: +31 (0)165 553911  
e-mail: Service@interflon.com  
Website: www.interflon.com

e-mail (competent person)	Service@interflon.com (Service lab)
---------------------------	-------------------------------------

#### 1.4 Emergency telephone number

Poison centre					
Country	Name	Postal code/ city	Telephone	Telefax	Opening hours
United Kingdom	UK National Poison Centre		UK National Poisons Emergency number: +44 870 600 6266		Mon - Fri 12:00 AM - 11:00 PM

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Category	Hazard class and category	Hazard statement
2.3	aerosols	1	Aerosol 1	H222,H229
3.3	serious eye damage/eye irritation	2	Eye Irrit. 2	H319

For full text of abbreviations: see SECTION 16.

#### 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

- Signal word. danger

- Pictograms

GHS02, GHS07



## Interflon Lube TF (Aerosol)

**Version number:**

5.6

Replaces version: (5)

25.02.2021

25.02.2021:

### - Hazard statements

H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H319 Causes serious eye irritation.

### - Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/....  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337+P313 If eye irritation persists: Get medical advice/attention.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

### - Supplemental hazard information

EUH066 Repeated exposure may cause skin dryness or cracking.

### Additional labelling according to Directive 75/324/EEC relating to aerosol dispensers

Extremely flammable. Pressurized container: may burst if heated. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

## 2.3 Other hazards

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not relevant (mixture)

### 3.2 Mixtures

Product description

Mixture of mineral and vegetable oils, additives and Micpol®

Hazardous ingredients

Name of substance	Identifier	Wt%	Classification acc. to GHS	Notes
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	CAS No 64742-48-9  EC No 918-481-9  REACH Reg. No 01-2119457273-39-xxxx	25 – < 50	Asp. Tox. 1 / H304	
butane	CAS No 106-97-8  EC No 203-448-7  Index No 601-004-00-0  REACH Reg. No 01-2119474691-32-xxxx	10 – < 25	Flam. Gas 1 / H220 Press. Gas C / H280	C(a) K(b)

## Interflon Lube TF (Aerosol)

**Version number:**

25.02.2021

25.02.2021:

5.6

Replaces version: (5)

Name of substance	Identifier	Wt%	Classification acc. to GHS	Notes
Propane	CAS No 74-98-6  EC No 200-827-9  Index No 601-003-00-5  REACH Reg. No 01-2119486944-21-xxxx	5 – < 10	Flam. Gas 1 / H220 Press. Gas L / H280	
isobutane	CAS No 75-28-5  EC No 200-857-2  Index No 601-004-00-0  REACH Reg. No 01-2119485395-27-xxxx	5 – < 10	Flam. Gas 1 / H220 Press. Gas C / H280	C(a) GHS-HC U
Distillates (petroleum), hydro-treated heavy paraffinic	CAS No 64742-54-7  EC No 265-157-1  Index No 649-467-00-8  REACH Reg. No 01-2119484627-25-xxxx	1 – < 5	Asp. Tox. 1 / H304	GHS-HC L(b)
(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine	CAS No 110-25-8  EC No 203-749-3  REACH Reg. No 01-2119488991-20	1 – < 5	Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Eye Dam. 1 / H318 Aquatic Acute 1 / H400	

**Notes**

C(a): Mixture of isomers

GHS-HC: Harmonised classification (the classification of the substance corresponds to the entry in the list according to 1272/2008/EC, Annex VI)

K(b): The classification as a carcinogen or mutagen is not required. The substance contains less than 0,1 % w/w 1,3-butadiene (EINECS No 203-450-8). If the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-) P210-P403 should apply

L(b): The classification as a carcinogen is not required. The substance contains less than 3 % DMSO extract

U: When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

**Regulation 648/2004/EC on detergents**

Wt%	Constituents	Weight % content (or range)
≥15% - <30%	aliphatic hydrocarbons	15 % or over but less than 30 %

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

## Interflon Lube TF (Aerosol)

**Version number:**  
5.6  
Replaces version: (5)

25.02.2021

25.02.2021:

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

##### General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

##### Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

##### Following skin contact

Wash with plenty of soap and water.

##### Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

##### Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

#### 4.3 Indication of any immediate medical attention and special treatment needed

none

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

##### Suitable extinguishing media

Water mist, Fire extinguishing powder

##### Unsuitable extinguishing media

Water jet

#### 5.2 Special hazards arising from the substance or mixture

##### Hazardous combustion products

Nitrogen oxides (NO<sub>x</sub>), Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance. Use suitable breathing apparatus.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

##### For non-emergency personnel

Remove persons to safety.

##### For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

## Interflon Lube TF (Aerosol)

Version number:

25.02.2021

25.02.2021:

5.6

Replaces version: (5)

### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

### 6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Remove contaminated clothing and protective equipment before entering eating areas. Never place chemicals in containers that are normally used for food or drink.

### 7.2 Conditions for safe storage, including any incompatibilities

Conditions of storage

Store in accordance with local/regional/national/international regulations. Keep container tightly closed and in a well-ventilated place.

Managing of associated risks

- Flammability hazards

Do not spray on an open flame or other ignition source. Protect from sunlight. Keep in a cool place.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to ADR) may be used.

### 7.3 Specific end use(s)

See section 16 for a general overview.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
GB	butane	106-97-8	WEL	600	1,450	750	1,810				EH40/2005

Notation

Ceiling-C

STEL

TWA

ceiling value is a limit value above which exposure should not occur  
short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)  
time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours  
time-weighted average (unless otherwise specified)

## Interflon Lube TF (Aerosol)

**Version number:**  
5.6  
Replaces version: (5)

25.02.2021

25.02.2021:

no data available

### 8.2 Exposure controls

#### General safety precautions

Use only in well-ventilated areas.  
In case of insufficient ventilation, wear suitable respiratory equipment.  
Avoid contact with skin and eyes.  
Keep away from food, drink and animal feedingstuffs. Do not breathe gas/vapour/spray. Wash hands after use.

#### Individual protection measures (personal protective equipment)

##### Eye/face protection

Use safety goggles with side protection.

##### Skin protection

###### - Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits.

###### - Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

##### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

##### Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	liquid, gaseous (spray aerosol)
Colour	yellowish brown
Odour	Like oil
Melting point/freezing point	not determined
Boiling point or initial boiling point and boiling range	<0 °C at 1,013 hPa
Flammability	flammable aerosol in accordance with GHS criteria
Lower and upper explosion limit	1.5 vol% - 10 vol%
Flash point	<-60 °C at 1 atm
Auto-ignition temperature	>370 °C (auto-ignition temperature (liquids and gases))
Decomposition temperature	not relevant
pH (value)	not determined

## Interflon Lube TF (Aerosol)

**Version number:**  
5.6  
Replaces version: (5)

25.02.2021

25.02.2021:

Kinematic viscosity	not relevant
Solubility(ies)	not determined

### Partition coefficient

Partition coefficient n-octanol/water (log value)	this information is not available
---	-----------------------------------

Vapour pressure	3,800 hPa at 20 °C
-----------------	--------------------

### Density and/or relative density

Density	0.73 g/cm <sup>3</sup> at 20 °C
Relative vapour density	information on this property is not available

Particle characteristics	not relevant (aerosol)
--------------------------	------------------------

## 9.2 Other information

Information with regard to physical hazard classes

Aerosols

- Components (flammable)	27.3 %
--------------------------	--------

### Other safety characteristics

Temperature class (EU, acc. to ATEX)	T2 (maximum permissible surface temperature on the equipment: 300°C)
--------------------------------------	--

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

### 10.2 Chemical stability

See below "Conditions to avoid".

### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

### 10.4 Conditions to avoid

Do not spray on an open flame or other ignition source. Keep away from heat.

Hints to prevent fire or explosion

Protect from sunlight.

### 10.5 Incompatible materials

Oxidisers

## Interflon Lube TF (Aerosol)

**Version number:**  
5.6  
Replaces version: (5)

25.02.2021

25.02.2021:

### 10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Test data are not available for the complete mixture.

#### Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### Classification according to GHS (1272/2008/EC, CLP)

##### Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture			
Name of substance	CAS No	Exposure route	ATE
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	inhalation: dust/mist	2.18 mg/l/4h
(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine	110-25-8	inhalation: vapour	18.33 mg/l/4h

##### Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

##### Serious eye damage/eye irritation

Causes serious eye irritation.

##### Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

##### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

##### Carcinogenicity

Shall not be classified as carcinogenic.

##### Reproductive toxicity

Shall not be classified as a reproductive toxicant.

##### Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

##### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

##### Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

##### Other information

Repeated exposure may cause skin dryness or cracking.

### 11.2 Information on other hazards

There is no additional information.



## Interflon Lube TF (Aerosol)

**Version number:**  
5.6  
Replaces version: (5)

25.02.2021

25.02.2021:

### SECTION 12: Ecological information

#### 12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

#### 12.2 Persistence and degradability

Data are not available.

#### 12.3 Bioaccumulative potential

Data are not available.

#### 12.4 Mobility in soil

Data are not available.

#### 12.5 Results of PBT and vPvB assessment

Data are not available.

#### 12.6 Endocrine disrupting properties

None of the ingredients are listed.

#### 12.7 Other adverse effects

Data are not available.

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

#### Relevant provisions relating to waste

List of wastes

- Product

13 02 08\* other engine, gear and lubricating oils

15 01 04 metallic packaging

16 05 04\* gases in pressure containers (including halons) containing hazardous substances

#### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

### SECTION 14: Transport information

#### 14.1 UN number or ID number

ADR/RID/ADN

UN 1950

IMDG-Code

UN 1950

ICAO-TI

UN 1950

#### 14.2 UN proper shipping name

ADR/RID/ADN

AEROSOLS

## Interflon Lube TF (Aerosol)

**Version number:**

5.6

Replaces version: (5)

25.02.2021

25.02.2021:


IMDG-Code	AEROSOLS
ICAO-TI	Aerosols, flammable
<b>14.3 Transport hazard class(es)</b>	
ADR/RID/ADN	2 (2.1)
IMDG-Code	2.1
ICAO-TI	2.1
<b>14.4 Packing group</b>	not assigned
<b>14.5 Environmental hazards</b>	non-environmentally hazardous acc. to the dangerous goods regulations
<b>14.6 Special precautions for user</b>	
Provisions for dangerous goods (ADR) should be complied within the premises.	
<b>14.7 Maritime transport in bulk according to IMO instruments</b>	
The cargo is not intended to be carried in bulk.	

### Information for each of the UN Model Regulations

#### **Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - Additional information**

Classification code	5F
Danger label(s)	2.1
	
Special provisions (SP)	190, 327, 344, 625
Excepted quantities (EQ)	E0
Limited quantities (LQ)	1 L
Transport category (TC)	2
Tunnel restriction code (TRC)	D

#### **International Maritime Dangerous Goods Code (IMDG) - Additional information**

Marine pollutant	-
Danger label(s)	2.1
	
Special provisions (SP)	63, 190, 277, 327, 344, 381, 959
Excepted quantities (EQ)	E0
Limited quantities (LQ)	1 L
EmS	F-D, S-U
Stowage category	-

## Interflon Lube TF (Aerosol)

Version number:

25.02.2021

25.02.2021:

5.6

Replaces version: (5)

### International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Danger label(s)

2.1



Special provisions (SP)

A145, A167

Excepted quantities (EQ)

E0

Limited quantities (LQ)

30 kg

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

##### Relevant provisions of the European Union (EU)

##### Restrictions according to REACH, Annex XVII

Dangerous substances with restrictions (REACH, Annex XVII)				
Name of substance	Name acc. to inventory	CAS No	Restriction	No
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC		R3	3
(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine	this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC		R3	3
Propane	flammable / pyrophoric		R40	40
butane	flammable / pyrophoric		R40	40
isobutane	flammable / pyrophoric		R40	40

##### Legend

R3

1. Shall not be used in:
  - ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
  - tricks and jokes,
  - games for one or more participants, or any article intended to be used as such, even with ornamental aspects,
2. Articles not complying with paragraph 1 shall not be placed on the market.
3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:
  - can be used as fuel in decorative oil lamps for supply to the general public, and
  - present an aspiration hazard and are labelled with H304.
4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).
5. Without prejudice to the implementation of other Union provisions relating to the classification, labelling and packaging of substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:
  - (a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil – or even sucking the wick of lamps – may lead to life-threatening lung damage";
  - (b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: 'Just a sip of grill lighter fluid may lead to life threatening lung damage';
  - (c) lamps oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.;

## Interflon Lube TF (Aerosol)

**Version number:**

25.02.2021

25.02.2021:

5.6

Replaces version: (5)

### Legend

R40

1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:

- metallic glitter intended mainly for decoration,

- artificial snow and frost,

- 'whoopie' cushions,

- silly string aerosols,

- imitation excrement,

- horns for parties,

- decorative flakes and foams,

- artificial cobwebs,

- stink bombs.

2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:

'For professional users only'.

3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/324/EEC (2).

4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.

### Seveso Directive

2012/18/EU (Seveso III)			
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements	Notes
P3a	flammable aerosols (containing Flam. Gas or Flam. Liq.)	150                      500	46)

### Notation

46) 'flammable' aerosols category 1 or 2, containing flammable gases category 1 or 2 or flammable liquids category 1

Note: qualifying quantity = net

### Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

none of the ingredients are listed

### Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

none of the ingredients are listed

### Water Framework Directive (WFD)

List of pollutants (WFD)			
Name of substance	CAS No	Listed in	Remarks
Distillates (petroleum), hydrotreated heavy paraffinic		A)	

### Legend

A)

Indicative list of the main pollutants

### Regulation on persistent organic pollutants (POP)

None of the ingredients are listed.

## Interflon Lube TF (Aerosol)

Version number:

5.6

Replaces version: (5)

25.02.2021

25.02.2021:

### National inventories

Country	Inventory	Status
CA	DSL	not all ingredients are listed
EU	REACH Reg.	all ingredients are listed or exempt from listing
US	TSCA	not all ingredients are listed

#### Legend

DSL Domestic Substances List (DSL)  
REACH Reg. REACH registered substances  
TSCA Toxic Substance Control Act

## 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information

#### Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
3.2		Hazardous ingredients: change in the listing (table)	yes
3.2		Regulation 648/2004/EC on detergents	yes
3.2		Regulation 648/2004/EC on detergents: change in the listing (table)	yes
5.1	Suitable extinguishing media: Water spray, BC-powder	Suitable extinguishing media: Water mist, Fire extinguishing powder	yes
5.3	Advice for firefighters: In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.	Advice for firefighters: In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance. Use suitable breathing apparatus.	yes
7.1	Advice on general occupational hygiene: Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.	Advice on general occupational hygiene: Remove contaminated clothing and protective equipment before entering eating areas. Never place chemicals in containers that are normally used for food or drink.	yes
7.2	- Flammability hazards: Do not spray on an open flame or other ignition source. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.	- Flammability hazards: Do not spray on an open flame or other ignition source. Protect from sunlight. Keep in a cool place.	yes
8.2	General safety precautions: Use only in well-ventilated areas. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin and eyes. Do not eat, drink and smoke in work areas.	General safety precautions: Use only in well-ventilated areas. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin and eyes. Keep away from food, drink and animal feedingstuffs. Do not breathe gas/vapour/spray. Wash hands after use.	yes

## Interflon Lube TF (Aerosol)

Version number:

5.6

Replaces version: (5)

25.02.2021

25.02.2021:

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
8.2	Eye/face protection: Use protective eyewear to guard against splash of liquids.	Eye/face protection: Use safety goggle with side protection.	yes
8.2	Hand protection: When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. Type of material. NBR: acrylonitrile-butadiene rubber. CR: chloroprene (chlorobutadiene) rubber. PVC: polyvinyl chloride.	Hand protection: When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits.	yes

### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
Acute Tox.	Acute toxicity
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR	Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
ADR/RID/ADN	European Agreements concerning the International Carriage of Dangerous Goods by Road/Rail/Inland Waterways (ADR/RID/ADN)
Aquatic Acute	Hazardous to the aquatic environment - acute hazard
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
DGR	Dangerous Goods Regulations (see IATA/DGR)
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EH40/2005	EH40/2005 Workplace exposure limits ( <a href="http://www.nationalarchives.gov.uk/doc/open-government-licence/">http://www.nationalarchives.gov.uk/doc/open-government-licence/</a> )
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Gas	Flammable gas
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)

## Interflon Lube TF (Aerosol)

**Version number:**

5.6

Replaces version: (5)

25.02.2021

25.02.2021:

Abbr.	Descriptions of used abbreviations
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
ppm	Parts per million
Press. Gas	Gas under pressure
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
TWA	Time-weighted average
UFI	Unique formula identifier
vPvB	Very Persistent and very Bioaccumulative
WEL	Workplace exposure limit

### Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

### Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

### List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.

## Interflon Lube TF (Aerosol)

**Version number:**  
5.6  
Replaces version: (5)

25.02.2021

25.02.2021:

Code	Text
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.

### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.